

No.	DATE	REVISION
1	7/20/94	MISC.
2	9/8/94	ADDED DRAINAGE PIPE
3	8/24/95	AS-BUILT DRAWING

**CLA Engineers, Inc.**  
Civil • Structural • Surveying

317 MAIN STREET NORMICH, CT 06360  
(203) 886-1985 FAX (203) 886-9165

**TOWN OF MONTVILLE**  
**MONTVILLE LANDFILL**  
**CLOSURE**

**DETAILS**

PROJECT No.  
**CL-91-969**

DRAWN BY:  
**T.A.W.**

APPROVED BY:  
**R.A.D.**

DATE:  
**JULY 1994**

SHEET No.  
**2 OF 2**

**Project:** Montville Landfill  
**Location:** Montville, CT  
**WSE Project No.:** ENG23-0165  
**Calculation:** 02 - Verneer Stability at top of landfill



55 Walkers brook Dr., Reading, MA 01867 (HQ)  
 Tel: 978.532.1900

Calc. By: J. MacGregor, 6/05/23  
 Check By: J. Laird, 6/15/23

### MONTVILLE LANDFILL SOLAR - GEOTECHNICAL CALCULATIONS

#### LANDFILL VEENER STABILITY EVALUATION

$$FS = \frac{[(t-h)Y_s + hY_{sat} - hY_w]}{[(t-h)Y_s + hY_{sat}]} \times \frac{\tan \phi}{\tan \beta}$$

(From R. Theil - Slope Stability Sensitivity of Final Covers - The First Pan American Conference & Exhibition, 2008)

Veneer Stability for 18 Percent Slope

Input

t = thickness of cover soils above FML (ft.)	0.5	Based on 1994 drawings
h = water depth above FML (= t for fully saturated conditions) (ft.)	0.5	
Y <sub>s</sub> = dry unit weight of cover soils (topsoil)	90	
Y <sub>sat</sub> = saturated unit weight of cover soils (topsoil)	115	
Y <sub>w</sub> = unit weight of water	62.4	
φ = Interface friction angle between sand drainage and clay liner	32	Stark (2021) softened clay, PI = 25 (assumed)
β = Slope angle	6 H:1V	
	0.17	radians
	9.5	Degrees
	~10.5	% Slope

FS = 1.7

# Unpaved Road & Subgrade Stabilization Application Suggestion Summary

**Tensar**


Design		Reference	
Project		Location	
Customer		Designer	Jennifer MacGregor
Company	Weston & Sampson Engineers, Inc.	Date	June 13, 2023

Input checked by J. Laird, 05/15/2023

## Design Methodology

The Lees Approach to Applied Mechanical Stabilization for stabilizing soft subgrades to support construction and in-service traffic by incorporating the true behavior of mechanically stabilized unbound aggregate layers subjected to dynamic stresses from vehicular loading.


## Results




	Stabilized	Unstabilized
Total thickness	9.5 in	22 in
Surface rut depth	1 in	1 in
Enhanced modulus, $M_r$	16,000 psi	
Required ESALs	1,100	1,100
Subgrade protection level	ADEQUATE	UNPROTECTED
Controlling design	Surface rut depth	Bearing capacity

Total cost	\$140,013	\$227,266
Unit cost	\$20.16/yd <sup>2</sup>	\$32.73/yd <sup>2</sup>
Construction time	8.2 days	17 days
Dump truck visits	383	885
Fuel required	2,043 gal	4,720 gal
Water required	45,822 gal	106,115 gal
Carbon emissions	86,310 lbCO <sub>2</sub> e	167,150 lbCO <sub>2</sub> e


## Construction Cost



## Construction Time



## Environmental Cost



## Parameters

### Construction Traffic

Axle load	18 kip
Axle passes	1,000
Tire width	385 mm
Tire pressure	110 psi
Wheel configuration	Single wheel
Wander	3 ft

### In-Service Traffic

Axle load	18 kip
Axle passes	100
Tire width	295 mm
Tire pressure	110 psi
Wheel configuration	Dual wheel
Wander	3 ft

### Aggregate

Unit weight	135 pcf
Surface rut depth	1 in
D <sub>100</sub>	3 in
D <sub>50</sub>	1.2 in

### Subgrade

Soil type	Clay
Plasticity	High (CH)
CBR	1.5%
Separation geosynthetic	No
Subgrade protection level	Adequate

### Dimensions

Project area	62,500 ft <sup>2</sup>
--------------	------------------------

### Material Costs

Aggregate cost	\$25.00/ton
----------------	-------------

### Geosynthetic Costs

NX850	\$6.03/yd <sup>2</sup>
-------	------------------------

### Grading Requirements

Grade offset	Meet existing grade
Excavation cost	\$8.00/yd <sup>3</sup>

## Specification

To protect the performance and value achieved, a specification is generated/attached to accompany the completed design. The content of the specification provides the most effective protection to the achieved performance in a format that can be used within any project documentation.

## Supporting Documents

To provide further support and advice for your completed Tensar design, documents relating to this application can be found in the "Resources" section of Tensar+. These include installation advice, background to the available value and project case studies.

This report was prepared using Tensar+ (2.8.2)  
© 1998-2023 Tensar International Corporation. All rights reserved. Tensar is a registered trademark.

### Limitations of this Report

You undertake to only use the Tensar+ software tool and its output solely to evaluate the application of Tensar geogrids, and strictly according to the Terms of Use. The suitability of the software output and Tensar International's geogrids for any project is the sole responsibility of you, and your employees, contractors or other third parties who access the Tensar+ software tool and its output ("Your Associates"). The Tensar+ software output is merely illustrative and is not a detailed design. You will ensure that you and Your Associates have undergone all necessary training through Tensar International and/or have the necessary expertise and experience to use the Tensar+ software tool and its output correctly and safely. Copyright in the Tensar+ software output belongs to Tensar International. It may not be reproduced in whole or in part without the prior written permission of Tensar International except to Your Associates provided it is only disclosed for the purpose of evaluating the commercial application for the use of Tensar International's geogrids, and you are fully liable for Your Associates' acts or omissions. The Tensar+ software output does not form the whole or any part of a contract.

## Test Pit Information

P:\Private\Verogy Solar\Montville, CT Landfill\Design\Geotechnical\Figures\Figure 2 - Site Plan.dwg



Weston & Sampson Engineers, Inc.  
55 Walkers Brook Drive, Suite 100  
Reading, MA 01867  
978.532.1900 800.SAMPSON  
www.westonandsampson.com


NOTES

1. THIS PLAN IS BASED ON A PROPOSED SITE PLAN PREPARED BY WESTON & SAMPSON ENGINEERS, INC. DATED MAY 2023.
2. TEST PITS WERE COMPLETED BY WESTON & SAMPSON ENGINEERS ON JUNE 2, 2023.
3. TEST PIT LOCATIONS WERE LOCATED USING A HANDHELD GPS.

LEGEND

TP-X  
DESIGNATION AND APPROXIMATE LOCATION OF TEST PIT



GRAPHIC SCALE




ORIENTATION		TITLE	
		SITE PLAN	
		PROJECT	
		MONTVILLE LANDFILL SOLAR	
		669 ROUTE 163 MONTVILLE, CT 06353	
		FIGURE 2	
DATE	06/2023		
DRWN BY	AC		
CHKD BY	DD		
PRJ. NO.	ENG23-0165		
REV. NO.	-		



CONTRACTOR: <b>Weston &amp; Sampson Engineers</b>	TEST PIT LOCATION: <b>See Attached Figure</b>	DATE START: <b>June 2, 2023</b>
OPERATOR: <b>A. Chabot</b>	PLAN DIMENSIONS: <b>Length: 1.5 ft. , Width: 1.5 ft.</b>	DATE FINISH: <b>June 2, 2023</b>
LOGGED BY: <b>A. Chabot</b>	SEEPAGE REMARKS: <b>No Seepage Observed</b>	GROUND EL: <b>Not Available</b>
CHECKED BY: <b>T. Blair, PE</b>	CAVING REMARKS: <b>No Caving Observed</b>	FINAL DEPTH: <b>2.0 ft.</b>
EQUIPMENT: <b>Hand Shovel</b>	BACKFILL MATERIAL: <b>Excavated Soil</b>	GRID COORDS: <b>N:730178 ± / E:1162923 ±</b>
BUCKET TYPE: <b>N/A</b>	OTHER COMMENTS:	GRID SYSTEM: <b>NAD83 State Plane (CT)</b>

DEPTH BELOW GROUND SURFACE [VERTICAL FT.]	SAMPLE TYPE GRAPHIC	STRATIGRAPHY LOG	STRATUM IDENTIFICATION AND DESCRIPTION	ELEVATION SCALE SHOWN TO NEAREST FT.	REMARKS, OTHER TESTS, AND INSTALLATIONS
			Surface: Grass area.		Note: Values in brackets preceeding a remark indicate depth below ground surface (in feet) corresponding to the remark.
	G		<b>Silty sand (SM)</b> - Dark brown; mostly fine to medium SAND, some non plastic fines; common roots and wood chips. <b>[VEGETATIVE SUPPORT]</b>		
	G		<b>Well graded sand with gravel (SW)</b> - Light brown; moist; mostly fine to coarse SAND, little fine to coarse gravel, trace non plastic fines.		
5				-5	<b>Exploration ended at 2.0 ft.</b> Top of landfill cap not encountered.

CONTRACTOR: <b>Weston &amp; Sampson Engineers</b>	TEST PIT LOCATION: <b>See Attached Figure</b>	DATE START: <b>June 2, 2023</b>
OPERATOR: <b>A. Chabot</b>	PLAN DIMENSIONS: <b>Length: 1.5 ft. , Width: 1.5 ft.</b>	DATE FINISH: <b>June 2, 2023</b>
LOGGED BY: <b>A. Chabot</b>	SEEPAGE REMARKS: <b>No Seepage Observed</b>	GROUND EL: <b>Not Available</b>
CHECKED BY: <b>T. Blair, PE</b>	CAVING REMARKS: <b>No Caving Observed</b>	FINAL DEPTH: <b>2.0 ft.</b>
EQUIPMENT: <b>Hand Shovel</b>	BACKFILL MATERIAL: <b>Excavated Soil</b>	GRID COORDS: <b>N:730125 ± / E:1162945 ±</b>
BUCKET TYPE: <b>N/A</b>	OTHER COMMENTS:	GRID SYSTEM: <b>NAD83 State Plane (CT)</b>

DEPTH BELOW GROUND SURFACE [VERTICAL FT.]	SAMPLE TYPE GRAPHIC	STRATIGRAPHY LOG	STRATUM IDENTIFICATION AND DESCRIPTION	ELEVATION SCALE SHOWN TO NEAREST FT.	REMARKS, OTHER TESTS, AND INSTALLATIONS
			Surface: Grass area.		Note: Values in brackets preceeding a remark indicate depth below ground surface (in feet) corresponding to the remark.
	G		<b>Silty sand with gravel (SM)</b> - Brown; moist; mostly fine to coarse SAND, little fine to coarse gravel, little non plastic fines; occasional debris (asphalt), trace debris (brick, plastic, glass). <b>[VEGETATIVE SUPPORT]</b>		
5				-5	<b>Exploration ended at 2.0 ft.</b> Top of landfill cap not encountered.

# GUIDE TO SUBSURFACE EXPLORATION LOGS



# INDEX SHEET 1 GENERAL INFORMATION

## GENERAL NOTES AND USE OF LOGS

- 1.) Explorations were made by ordinary and conventional methods and with care adequate for Weston & Sampson's study and/or design purposes. The exploration logs are part of a specific report prepared by Weston & Sampson for the referenced project and client, and are an integral part of that report. Information and interpretations are subject to the explanations and limitations stated in the report. Weston & Sampson is not responsible for any interpretations, assumptions, projections, or interpolations made by others.
- 2.) Exploration logs represent general conditions observed at the point of exploration on the date(s) stated. Boundary lines separating soil and rock layers (strata) represent approximate boundaries only and are shown as solid lines where observed and dashed lines where inferred based on drilling action. Actual transitions may be gradual and changes may occur over time.
- 3.) Soil and rock descriptions are based on visual-manual examination of recovered samples, direct observation in test pits (when permissible), and laboratory testing (when conducted).
- 4.) Water level observations were made at the times and under the conditions stated. Fluctuations should be expected to vary with seasons and other factors. Use of fluids during drilling may affect water level observations. The absence of water level observations does not necessarily mean the exploration was dry or that subsurface water will not be encountered during construction.
- 5.) Standard split spoon samplers may not recover particles with any dimension larger than 1-3/8 inches. Reported gravel conditions or poor sample recovery may not reflect actual in-situ conditions.
- 6.) Sections of this guide provide a general overview of Weston & Sampson's practices and procedures for *identifying* and *describing* soil and rock. These procedures are predominantly based on ASTM D2488, *Standard Practice for Description and Identification of Soils (Visual-Manual Procedures)*, the International Society of Rock Mechanics (ISRM) standards, and the *Engineering Geology Field Manual* published by the Bureau of Reclamation. Not all aspects of this guide relating to description and identification procedures of soil and rock may be applicable in all circumstances.

## SAMPLER GRAPHICS

- Split Spoon (Standard)  
2" OD, 1-3/8" ID
- Split Spoon (Oversize)  
3" OD, 2-3/8" ID
- Shelby or Piston Tube  
3" OD, 2-7/8" ID
- Double-Tube Rock Core Barrel  
2" Core Diameter
- Direct Push with Acetate Liner  
Various Liner Sizes
- Auger Sample  
(from cuttings or hand auger)
- Grab Sample  
(manual, from discrete point)
- Composite Sample  
(multiple grab samples)

## WELL GRAPHICS

- Cement concrete seal around casing or riser pipe
- Bentonite seal around casing or riser pipe
- Cement grout seal around casing or riser pipe
- Soil backfill around riser pipe or beneath screen
- Gravel backfill around screen or riser pipe
- Sand backfill around screen or riser pipe (filter sand)
- Solid-wall riser; Sch. 40 PVC, 1" ID unless noted otherwise
- Slotted screen; Sch. 40 PVC, 1" ID with machined slots

## CAVING / SEEPAGE TERMS

The following caving and/or seepage terms may appear on a test pit log.

Caving Term	Criteria
Minor.....	less than 1 cubic ft.
Moderate.....	1 to 3 cubic ft.
Severe.....	greater than 3 cubic ft.

Seepage Term	Criteria
Slow.....	less than 1 gpm
Moderate.....	1 to 3 gpm
Fast.....	greater than 3 gpm

## KEY TO WATER LEVELS

- Observed in exploration during advancement.
- Measured in exploration at completion, prior to backfilling or well installation.
- Measured in exploration after the stated stabilization period, prior to backfilling, or in well installation if noted.

## DEFINITIONS OF COMMON TERMS

**Sample Recovery Ratio** - The length of material recovered in a drive or push type sampler over the length of sampler penetration, in inches (e.g. 18/24).

**Standard Penetration Test (SPT)** - An in-situ test where a standard split-spoon sampler is driven a distance of 12 or 18 inches (after an initial 6-inch seating interval) using a 140-lb. hammer falling 30 inches for each blow.

**SPT Blows** - The number of hammer blows required to drive a split-spoon sampler each consecutive 6-inch interval during a *Standard Penetration Test*. If no discernable advancement of a split spoon sampler is made after 50 consecutive hammer blows, 50/X indicates *sampler refusal* and is the number of blows required to drive the sampler X inches.

**SPT N-Value (N)** - The uncorrected blow count representation of a soil's penetration resistance over a 12-inch interval after an initial 6-in. seating interval, reported in blows per foot (bpf). The N-value is correlated to soil engineering properties.

**Auger Refusal** - No discernable advancement of the auger over a period of 5 minutes with full rig down pressure applied.

**Casing Refusal (Driven)** - Casing penetration of less than 6 inches after a minimum 50 blows of a drop hammer weighing 300 lbs. or a minimum 100 blows of a drop hammer weighing 140 lbs.

**PID Measurement** - A measurement (electronic reading) taken in the field using a photoionization detector (PID) to detect the presence of volatile organic compounds in a soil sample. Values are reported as benzene equivalent units in parts per million (ppm) unless noted otherwise.

**Rock Quality Designation (RQD)** - A qualitative index measure of the degree of jointing and fracture of a rock core taken from a borehole. The RQD is defined as the sum length of solid core pieces 4 inches or longer divided by the run (cored) length, expressed as a percentage. Higher RQD values may indicate fewer joints and fractures in the rock mass.

**Fill (Made Ground)** - A deposit of soil and/or artificial waste materials that has been placed or altered by human processes.

## LABORATORY TESTS AND FIELD MEASUREMENTS

MC.....	Moisture Content	IC.....	1D Incremental Consolidation
OC.....	Organic Content	VS.....	Laboratory Vane Shear
PL.....	Plastic Limit	US.....	Unconfined Compression
LL.....	Liquid Limit	TC.....	Triaxial Compression
GC.....	Gravel Content	PP.....	Pocket (Hand) Penetrometer
SC.....	Sand Content	TV.....	Torvane (Hand Vane)
FC.....	Fines Content	PID.....	Photoionization Detector
DS.....	Direct Shear	FID.....	Flame Ionization Detector

## BORING ADVANCEMENT METHODS

**Hollow-Stem Auger Drilling** - Utilizes continuous flight auger sections with hollow stems to advance the borehole. Drill rods and a plug are inserted into the auger stem to prevent the entrance of soil cuttings into the augers.

**Rotary Wash Drilling** - Utilizes downward pressure and rotary action applied to a non-coring bit while washing the cuttings to the surface using a circulating fluid injected down the drill rods. The borehole is supported with either steel casing or the drilling fluid. Where a casing is used, the borehole is advanced sequentially by driving the casing to the desired depth and then cleaning out the casing. The process of driving and cleaning the casing is commonly referred to as the 'drive-and-wash' technique.

**Continuous Sampling** - Includes a variety of methods and procedures during which the borehole is advanced via continuous recovery of soil samples. *Direct Push* sampling is a common method that uses static downward pressure combined with percussive energy to drive a steel mandrel into the ground at continuous intervals while recovering soil samples in disposable acetate liners.

**Rock Coring** - Utilizes downward pressure and rotary action applied to a core barrel equipped with a diamond-set or tungsten carbide coring bit. During conventional coring, the entire barrel is retrieved from the hole upon completion of a core run. Wireline coring allows for removal of the inner barrel assembly containing the actual core while the drill rods and outer barrel remain in the hole. Various types and sizes of core barrels and bits are used.



# GUIDE TO SUBSURFACE EXPLORATION LOGS



# INDEX SHEET 2 SOIL DESCRIPTION

## SOIL CONSTITUENTS

Naturally occurring soils consist of one or more of the following matrix constituents defined in terms of particle size.

Constituent	U.S. Sieve Size	Observed Size (in.)
Gravel (Coarse)	3/4 in. - 3 in.	3/4 - 3
Gravel (Fine)	No. 4 - 3/4 in.	1/5 - 3/4
Sand (Coarse)	No. 10 - No. 40	1/16 - 1/5
Sand (Medium)	No. 40 - No. 10	1/64 - 1/16
Sand (Fine)	No. 200 - No. 40	1/300 - 1/64
Fines (Silt or Clay)	Smaller than No. 200	Less than 1/300

## SOIL IDENTIFICATION

*Soil identification* refers to the grouping of soils with similar physical characteristics into a category defined by a **group name** and corresponding **group symbol** based on estimation of the matrix soil constituents to the nearest 5% and simple manual tests. Proportions of cobbles, boulders, and other non-matrix soil materials are not considered during this procedure but are included in the overall soil description if observed or thought to be present. Refer to the following descriptions and tables adapted from ASTM D2488.

**Coarse-Grained Soil** - Coarse-grained soils contain fewer than 50% fines and are identified based on the following table.

Primary Constituent	Fines Percent	Type of Fines and Gradation	Group Symbol	Group Name <sup>(1)</sup>
GRAVEL % gravel > 10% % sand	≤ 5%	well graded	GW	Well graded gravel
		poorly graded	GP	Poorly graded gravel
	10% to 45%	clayey well graded	GW-GC	Well graded gravel with clay
		clayey poorly graded	GP-GC	Poorly graded gravel with clay
		silty well graded	GW-GM	Well graded gravel with silt
		silty poorly graded	GP-GM	Poorly graded gravel with silt
SAND % sand ≥ 10% % gravel	≤ 5%	clay fines	GC	Clayey gravel
		silt fines	GM	Silty gravel
	10% to 45%	well graded	SW	Well graded sand
		poorly graded	SP	Poorly graded sand
		clayey well graded	SW-SC	Well graded sand with clay
		clayey poorly graded	SP-SC	Poorly graded sand with clay
		silty well graded	SW-SM	Well graded sand with silt
		silty poorly graded	SP-SM	Poorly graded sand with silt
	15% to 45%	clay fines	SC	Clayey sand
		silt fines	SM	Silty sand

<sup>(1)</sup> If soil is a gravel and contains 15% or more sand, add "with sand" to the group name. If soil is a sand and contains 15% of more gravel, add "with gravel" to the group name.

**Inorganic Fine-Grained Soil** - Fine-grained soils contain 50% or more fines and are identified based on the following table.

Plasticity Criteria	Dry Strength	Coarse Fraction S = Sand, G = Gravel	Group Symbol	Group Name <sup>(1)</sup>
Medium	Medium to high	< 15% S + G	CL	Lean clay
		≥ 30% % S ≥ % G	CL	Sandy lean clay
		S + G % S < % G	CL	Gravelly lean clay
Non-plastic	None to low	< 15% S + G	ML	Silt
		≥ 30% % S ≥ % G	ML	Sandy silt
		S + G % S < % G	ML	Gravelly silt
High	High to very high	< 15% S + G	CH	Fat clay
		≥ 30% % S ≥ % G	CH	Sandy fat clay
		S + G % S < % G	CH	Gravelly fat clay
Low to Medium	Low to medium	< 15% S + G	MH	Elastic silt
		≥ 30% % S ≥ % G	MH	Sandy elastic silt
		S + G % S < % G	MH	Gravelly elastic silt

<sup>(1)</sup> If soil contains 15% to 25% sand or gravel, add "with sand" or "with gravel" to the group name.

**Organic Fine-Grained Soil** - Fine-grained soils that contain enough organic particles to influence the soil properties are identified as Organic Soil and assigned the group symbol OL or OH.

**Highly Organic Soil (Peat)** - Soils composed primarily of plant remains in various stages of decomposition are identified as Peat and given the group symbol PT. Peat usually has an organic odor, a dark brown to black color, and a texture ranging from fibrous (original plant structure intact or mostly intact) to amorphous (plant structure decomposed to fine particles).

## SOIL DESCRIPTION

Soils are *described* in the following general sequence. Deviations may occur in some instances.

### Identification Components

(1) Group Name and Group Symbol

### Description Components

- (2) Consistency (Fine-Grained) or Apparent Density (Coarse-Grained)
- (3) Color (*note, the term "to" may be used to indicate a gradational change*)
- (4) Soil Moisture
- (5) Matrix Soil Constituents (Gravel, Sand, Fines)
  - ↳ Proportion (*by weight*), particle size, plasticity of fines, angularity, etc.
- (6) Non-Matrix Soil Materials and Proportions (*by volume*)
- (7) Other Descriptive Information (Unusual Odor, Structure, Texture, etc.)
- (8) [Geologic Formation Name or Soil Survey Unit]

## SPT N-VALUE CORRELATIONS

Consistency	SPT N-Value	Apparent Density	SPT N-Value
Very soft	0 - 2	Very loose	0 - 5
Soft	2 - 4	Loose	5 - 10
Medium stiff	4 - 8	Medium dense	10 - 30
Stiff	8 - 15	Dense	30 - 50
Very stiff	15 - 30	Very dense	> 50
Hard	> 30		

## SOIL MOISTURE

**Dry**..... Apparent absence of moisture; dry to the touch.  
**Moist**..... Damp but no visible water.  
**Wet**..... Visible free water; saturated.

## PROPORTIONS / PERCENTAGES

Proportions of gravel, sand, and fines (excluding cobbles, boulders, and other constituents) are stated in the following terms indicating a range of percentages by weight (to nearest 5%) of the minus 3-in. soil fraction and add up to 100%.

Proportions of cobbles, boulders, and other non-matrix soil materials including artificial debris, roots, plant fibers, etc. are stated in the following terms indicating a range of percentages by volume (to the nearest 5%) of the total soil.

<b>Mostly</b> .....	50% - 100%	<b>Numerous</b> .....	40% - 50%
<b>Some</b> .....	30% - 45%	<b>Common</b> .....	25% - 35%
<b>Little</b> .....	15% - 25%	<b>Occasional</b> .....	10% - 20%
<b>Few</b> .....	5% - 10%	<b>Trace</b> .....	Less than 5%
<b>Trace</b> .....	Less than 5%		

## PLASTICITY (FINES ONLY)

**Non-plastic**..... Dry specimen ball falls apart easily. Cannot be rolled into thread at any moisture content.  
**Low**..... Dry specimen ball easily crushed with fingers. Can be rolled into 1/8-in. thread with some difficulty.  
**Medium**..... Difficult to crush dry specimen ball with fingers. Easily rolled into 1/8-in. thread.  
**High**..... Cannot crush dry specimen ball with fingers. Easily rolled and re-rolled into 1/8-in. thread.

## COBBLES AND BOULDERS

**Cobbles** - Particles of rock that will pass a 12-in. square opening and be retained on a 3-in. sieve.

**Boulders** - Particles of rock that will not pass a 12-in. square opening.

*Note: Where the percentage (by volume) of cobbles and/or boulders cannot be accurately or reliably estimated, the terms "with cobbles", "with boulders", or "with cobbles and boulders" may be used to indicate observed or inferred presence.*

## GUIDE TO SUBSURFACE EXPLORATION LOGS



## INDEX SHEET 3 ROCK DESCRIPTION

### ROCK DEFINITION

Where reported on an exploration log, *rock* is defined as any naturally formed aggregate of mineral matter occurring in large masses or fragments. This definition of rock should not be taken as a replacement for any definitions relating to rock and/or rock excavation defined in construction documents. Intensely weathered or decomposed rock that is friable and can be reduced to gravel size particles or smaller by normal hand pressure is identified and described as soil. Poorly indurated formational materials which display both rock-like and soil-like properties are identified and described as rock followed by the soil description. In such cases, the term "poorly indurated" or "weakly cemented" is added to the rock name (e.g. weakly cemented sandstone).

### ROCK IDENTIFICATION

Rock is identified by a combination of *rock type* (igneous, metamorphic, or sedimentary) followed by the *rock name* (e.g. granite, schist, sandstone).

### ROCK DESCRIPTION

Rock descriptions are presented in the following general sequence. The detail of description is dictated by the complexity and objectives of the project.

#### Identification Components

(1) Rock Type and Name

#### Description Components

- (2) Rock Grain Size (*for clastic sedimentary rock*)
- (3) Crystal Size (*for igneous and metamorphic rock*)
- (4) Bedding Spacing (*for sedimentary rock*)
- (5) Color
- (6) Hardness and Weathering Descriptors
- (7) Fracture Density
- (8) [Geologic Formation Name]

### ROCK QUALITY DESIGNATION

$$RQD (\%) = \frac{\sum \text{Length of intact core pieces} \geq 4 \text{ inches}}{\text{Total length of core run (inches)}} \times 100$$

The RQD should correlate with the fracture density in most cases. Higher RQD values generally indicate fewer joints and fractures.

### GRAIN / CRYSTAL SIZE

#### Grain Size for Clastic Sedimentary Rock

The names of clastic sedimentary rocks are generally based on their predominant clast or grain size (e.g. fine sandstone, medium sandstone, coarse gravel conglomerate, cobble conglomerate, siltstone, claystone).

#### Crystal Size for Igneous and Metamorphic Rock

Grain Size Description	Average Crystal Size (in.)
Very coarse grained (pegmatitic)	Greater than or equal to 3/8
Coarse-grained	Between 3/16 and 3/8
Medium-grained	Between 1/32 and 3/16
Fine-grained	Between 1/250 and 1/32
Aphanitic	Less than or equal to 1/250

### BEDDING SPACING

Bedding Description	Thickness / Spacing
Massive	Less than 10 ft.
Very thickly bedded	3 ft. to 10 ft.
Thickly bedded	1 ft. to 3 ft.
Moderately bedded	4 in. to 1 ft.
Thinly bedded	1 in. to 4 in.
Very thinly bedded	1/4 in. to 1 in.
Laminated	Less than 1/4 in.

*Note: Bedding is generally only applicable to sedimentary or bedded volcanic rocks.*

### HARDNESS

Hardness	Criteria
Extremely hard	Cannot be scratched with a pocketknife or sharp pick. Can only be chipped with repeated heavy hammer blows.
Very hard	Cannot be scratched with a pocketknife or sharp pick with difficulty. Breaks with repeated heavy hammer blows.
Hard	Can be scratched with a pocketknife or sharp pick with difficulty. Breaks with heavy hammer blows.
Moderately hard	Can be scratched with a pocketknife or sharp pick with light or moderate pressure. Breaks with moderate hammer blows.
Moderately soft	Can be grooved 1/16 in. deep with a pocketknife or sharp pick with moderate or heavy pressure. Breaks with light hammer blow or heavy manual pressure.
Soft	Can be grooved or gouged easily with a pocketknife or sharp pick. Breaks with light to moderate manual pressure.
Very soft	Can be readily indented, grooved, or gouged with fingernail, or carved with a pocketknife. Breaks with light manual pressure.

### WEATHERING (INTACT ROCK)

Weathering Description	Discoloration and/or Oxidation	General Characteristics
Fresh	Body of rock and fracture surfaces are not discolored or oxidized.	Rock texture unchanged. Hammer rings when crystalline rocks are struck.
Slightly weathered	Discoloration or oxidation limited to surface of, or short distance from, fractures. Most surfaces exhibit minor to complete discoloration.	Rock texture preserved. Hammer rings when crystalline rocks are struck. Body of rock not weakened.
Moderately weathered	Discoloration or oxidation extends usually throughout. Fe-Mg minerals appear rusty. All fracture surfaces are discolored or oxidized.	Rock texture generally preserved. Hammer does not ring when rock is struck. Body of rock slightly weakened.
Intensely weathered	Discoloration or oxidation throughout. Feldspar and Fe-Mg minerals altered to clay to some extent. All fracture surfaces are discolored or oxidized and friable.	Rock texture altered by chemical disintegration. Can usually be broken with moderate to heavy manual pressure or by light hammer blow. Body of rock is significantly weakened.
Decomposed	Discoloration or oxidation throughout but resistant minerals such as quartz may be unaltered. All feldspar and Fe-Mg minerals are completely altered to clay.	Resembles a soil; partial or complete remnant rock structure may be preserved. Can be granulated by hand. Resistant minerals may present as stringers or dikes.

### FRACTURE DENSITY


Description	Observed Fracture Density
Unfractured	No fractures
Very slightly fractured	Core lengths greater than 3 ft.
Slightly fractured	Core lengths mostly from 1 ft. to 3 ft.
Moderately fractured	Core lengths mostly from 4 in. to 1 ft.
Intensely fractured	Core lengths mostly from 1 in. to 4 in.
Very intensely fractured	Mostly chips and fragments

*Note: Fracture density is based on the fracture spacing in recovered core, measured along the core axis (excluding mechanical breaks).*

## Stockpile Sample Results

These results are for the exclusive use of the client for whom they were obtained. This report only relates to items inspected and/or tested. No warranty, expressed or implied, is made.

## Particle Size Distribution Report



% +3"	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
0.0	27.2	12.8	4.8	23.0	23.0	9.2	

SIEVE SIZE OR DIAMETER	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
1 1/2"	100.0		
1"	85.8		
3/4"	72.8		
1/2"	68.7		
3/8"	65.7		
#4	60.0		
#10	55.2		
#20	43.3		
#40	32.2		
#60	23.9		
#100	16.3		
#200	9.2		

\* (no specification provided)

Soil Description  
Brown f-m SAND and f-c GRAVEL, trace Silt

PL= NP      Atterberg Limits      LL= NV      PI= NP  
Coefficients  
D<sub>90</sub>= 28.4163      D<sub>85</sub>= 24.9333      D<sub>60</sub>= 4.7779  
D<sub>50</sub>= 1.3205      D<sub>30</sub>= 0.3697      D<sub>15</sub>= 0.1345  
D<sub>10</sub>= 0.0810      C<sub>u</sub>= 58.98      C<sub>c</sub>= 0.35

Classification  
USCS= SP-SM      AASHTO= A-1-b  
Remarks

Source of Sample: Stockpile  
Sample Number: SP-1 / G-1

Date: 06.14.23

Thielsch Engineering Inc.

Cranston, RI

Client: Weston & Sampson  
Project: Montville Landfill Solar  
Montville, CT

Project No: ENG23-0165

Figure 23-S-B400

Tested By: AV / SF

Checked By: Andrew Vanasse






Stockpile 1



These results are for the exclusive use of the client for whom they were obtained. This report only relates to items inspect and/or tested. No warranty, expressed or implied, is made.

## Particle Size Distribution Report



% +3"	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
0.0	15.2	22.7	7.2	35.7	18.0	1.2	

SIEVE SIZE OR DIAMETER	PERCENT FINER	SPEC.* PERCENT	PASS? (X=NO)
2"	100.0		
1 1/2"	94.9		
1"	88.0		
3/4"	84.8		
1/2"	77.6		
3/8"	71.9		
#4	62.1		
#10	54.9		
#20	40.0		
#40	19.2		
#60	8.4		
#100	3.0		
#200	1.2		

\* (no specification provided)

Soil Description  
Brown f-c SAND and f-c GRAVEL, trace Silt

PL= NP      Atterberg Limits      LL= NV      PI= NP  
Coefficients  
D<sub>90</sub>= 28.8388      D<sub>85</sub>= 19.3280      D<sub>60</sub>= 3.7762  
D<sub>50</sub>= 1.4197      D<sub>30</sub>= 0.6063      D<sub>15</sub>= 0.3555  
D<sub>10</sub>= 0.2752      C<sub>u</sub>= 13.72      C<sub>c</sub>= 0.35

Classification  
USCS= SP      AASHTO= A-1-b  
Remarks

Source of Sample: Stockpile  
Sample Number: SP-2 / G-1

Date: 06.14.23

Thielsch Engineering Inc.

Cranston, RI

Client: Weston & Sampson  
Project: Montville Landfill Solar  
Montville, CT

Project No: ENG23-0165

Figure 23-S-B401

Tested By: AV / SF

Checked By: Andrew Vanasse



Stockpile 2

# Authorization Application for Disruption of a Solid Waste Disposal Area

## APPENDIX F

### Stormwater Calculations



westonandsampson.com

Weston & Sampson Engineers, Inc.  
712 Brook Street, Suite 103  
Rocky Hill, CT 06067  
tel. 860.513.1473

# REPORT

June 2023

VCP Montville LF, LLC

Town of Montville Landfill  
Solar PV Development

669 Oakdale Road (CT RT 163)  
Montville, CT 06353

**Stormwater Report**

## TABLE OF CONTENTS

Stormwater Report

Attachment A - Locus Map

Attachment B - NRCS Web Soil Survey Map & Report: Hydrologic Soils Group,  
FEMA FIRMette, NOAA Atlas 14 Rainfall Data

Attachment C - Drainage Area Maps & HydroCAD Report



**Applicant/Project Name:** VCF Montville LF, LLC  
Town of Montville Landfill Solar PV Development

**Project Location:** 669 Oakdale Road (CT RT 163), Montville, CT 06353

**Application Prepared by:**  
Firm: Weston & Sampson Engineers, Inc.  
Registered PE: Rob Bukowski, P.E.

## **Introduction**

Weston & Sampson Engineers, Inc. (Weston & Sampson) has prepared this stormwater report on behalf of VCP Montville LF, LLC (Verogy) to develop a ground mounted solar photovoltaic (PV) array at the closed landfill, located at 669 Oakdale Road (CT RT 163) in Montville, Connecticut.

The existing Town of Montville Landfill covers an area of approximately 8-acres within a property that is approximately 25.5 acres. The site is currently used as a transfer station and is bounded by Oakdale Road (CT RT 163) to the south, the Fox Family Cemetery to the west, Fox Brook and Oxoboxo Brook to the north, and Wheeler Pond to the east.

The capped landfill slopes to all sides at an approximate 30% slope with an un-maintained meadow/brush ground cover. The top of the existing landfill is currently being used as sand/gravel stockpile storage. The landfill is in the southwest section of the property and the transfer station is in the southeast section of the property. The southern entrance and transfer station areas are covered by pavement and broken bituminous asphalt. There is an existing unpaved access road leading from the southern entrance, traversing the landfill cap counterclockwise, which culminates atop the landfill cap.

Wetland delineations performed determined three existing wetlands are onsite. The first is a bordering vegetated wetland north of the landfill and associated with Fox Brook. The second is an isolated vegetated wetland to the southwest of the landfill associated with a low point past the toe of the slope of the landfill and crosses the property line. The third is a bordering vegetated wetland in the southeast corner of the site associated with a natural drainage path draining easterly towards Wheeler Pond.

The proposed project will have minimum impact within the 50-foot upland review area adjacent to on-Site wetlands, with only two small areas of the proposed project within the outermost edges of the upland review area. Stabilization and maintenance of the existing access road, if necessary, will occur within approximately 386 square feet of the upland review area on the western side of the site. Subsurface electrical conduit will run from the eastern side of the access road to above-ground utility poles. There is an area of approximately 531 square feet within the upland review area where the proposed trench will pass through. This disturbance will be temporary as, once the conduit is installed, the area will be stabilized and re-vegetated.

No part of the project area is within a Federal Emergency Management Agency National Flood Hazard Zone. A Zone-A Flood Hazard Zone is associated with Fox Brook to the north of the project area.

## **Proposed Project**

The proposed project includes deploying ground-mounted solar on the existing landfill cap. The total capacity of the proposed ground mounted solar installation is approximately 776 kilowatt (kW) direct current (DC) (600 kW alternating current (AC)).

The on-cap solar PV array is to be supported on precast concrete ballasted foundations and will have a low bearing pressure that is designed to maintain the integrity of the existing engineered landfill cap. Each block will be placed on dense-graded crushed stone to level the blocks to meet the foundation manufacturer's requirements. Panel racking will be installed above the precast concrete ballasted foundations and solar PV

modules will be attached to the racking. The series of PV panels will be connected using above ground cables, cable trays, and conduits that bring the wiring to a central equipment pad located atop the landfill cap directly east of the solar PV array.

A chain link fence is proposed atop the landfill cap to provide security and separation of any unqualified personnel from any electrical conductors, as required by the National Electric Code. The total area of the array within the fence limits is approximately 2.4 acres. The proposed fence will be supported on ballast blocks as opposed to ground-driven poles to protect the existing engineered landfill cap.

A Locus Map of the project location is included as Figure 1 in **Attachment A**.

### **Erosion and Sediment Control**

The erosion and sediment controls have been designed in accordance with the 2002 Connecticut Guidelines for Soil Erosion and Sediment Control. Straw wattle is proposed as the sediment barrier for perimeter controls. When used on the cap, sandbags will be used to weigh the straw wattle down if needed. Any piercing activities such as driving stakes in the ground to keep straw wattle in place is prohibited while on the landfill cap to not damage the cap. A construction entrance/exit is proposed where the existing access road meets the paved area south of the landfill. A concrete washout basin is proposed near the construction entrance/exit.

### **Stormwater Analysis**

Stormwater runoff patterns for the Town of Montville Landfill will not be altered as part of the proposed project. Existing and proposed peak design flows were assessed using the National Resources Conservation Service (NRCS) Technical Release 20 (TR-20) methodology. HydroCAD® version 10.20-2d stormwater modeling software was used to analyze stormwater conditions. It is a comprehensive hydrodynamic modeling program which analyzes and designs site hydrology, surface drainage systems, and storm drains. It can manage a variety of flow situations such as overland flow, drainage swales, ponds, and piping systems.

The National Resources Conservation Service (NRCS) Web Soil Survey database was used to determine the hydrologic soil group (HSG) for the onsite soils. Stormwater rainfall event data is derived from the National Oceanic and Atmospheric Administration (NOAA) Atlas 14 Precipitation Frequency data for the site. The 2-, 10-, 25-, and 100- year, 24-hour, Type-III storm events were used to compare post-development conditions to pre-development conditions. The NRCS report and NOAA data are included in **Attachment B**.

A summary of the analysis is provided below, the full stormwater model and drainage area maps are included in **Attachment C**.

### **Existing Stormwater Flow**

The Town of Montville Landfill does not have an existing stormwater management system and stormwater currently flows off the landfill cap in all directions via overland flow. The limits of the stormwater analysis for this project include the landfill cap, the southern paved area, the majority of the eastern transfer station area, and the northern meadow/woodlands between the landfill cap and Fox Brook. HSG-A, B, C and D soils are all determined to be onsite, and coverages were accounted for accordingly based on HSG soil boundaries.

Pre-development conditions have been modeled assuming the landfill cap has been maintained as it was designed with meadow coverage.

HSG-D soils are assumed to be consistent with the landfill limit of waste which is assumed to extend to the landfill toe of slope.

Four points of analysis, each with their own drainage area, were analyzed. Figure 2 of **Attachment C** displays the limits of each drainage area, flow paths, and existing ground covers. A description of each drainage area is below:

- **Drainage Area A** – Northern portion of the landfill draining northerly towards Fox Brook,
- **Drainage Area B** – Southwest portion of the landfill draining southwesterly offsite,
- **Drainage Area C** – Southern portion of the landfill draining southeasterly offsite,
- **Drainage Area D** – Eastern portion of the landfill draining easterly offsite towards Wheeler Pond

### Proposed Stormwater Flow

The stormwater analysis assumes the array concrete ballast blocks and equipment pad will be considered disconnected impervious area in the post-development stormwater model. Figure 3 of **Attachment C** displays the limits of each drainage area, flow paths, and proposed ground covers. The dimensions of the ballast blocks are assumed to be 2.5-ft wide by 9-ft long. Two ballast blocks will be used for each table with each table consisting of approximately 16 solar PV modules.

Stormwater flow patterns do not change based on the proposed solar PV layout as there are no proposed grading changes. Post-development drainage areas are denoted with a suffix of “1” and are consistent with pre-development drainage areas.

The post-development coverage conditions remain consistent with the pre-development conditions for the majority of the site. The only difference being minor trimming to the woods coverage in the northeast corner of the site, and the addition of the concrete ballast blocks and gravel turnaround areas as unconnected impervious coverage. These changes do not change the overall runoff curve numbers (CN) of the drainage areas.

The time of concentrations (Tc) are consistent from pre- to post- development conditions. All Tcs begin with 100-feet of sheet flow followed by shallow concentrated flow until flow reaches the drainage area boundary.

### Peak Discharge Summary

As the overall CN and Tc for each drainage area remain consistent from pre- to post-development conditions, the project results in no changes in peak runoff discharge rate or volume for all design storms. The pre- and post-development conditions comparative table reflecting the HydroCAD results are shown in Table 1 below.

The project considers the following as impervious coverage: the existing access road, the existing paved areas, the existing broken bituminous areas, the proposed gravel turnaround area atop the landfill, the proposed concrete ballast blocks for the array, and the proposed concrete equipment pad.

TABLE 1: PRE-, POST-DEVELOPMENT COMPARATIVE RESULTS							
OFF-SITE SUMMARY		FLOW			VOLUME		
Point of Analysis	24-hour Storm Event	Pre-Development Receiving Peak Runoff (cfs)	Post-Development Receiving Peak Runoff (cfs)	Difference in Peak Runoff (cfs)	Pre-Development Receiving Discharge Volume (af)	Post-Development Receiving Discharge Volume (af)	Difference in Volume (af)
POA-A Northern Wetland	2	7.73	7.73	0.00	0.610	0.610	0.000
	10	15.14	15.14	0.00	1.177	1.177	0.000
	25	20.05	20.05	0.00	1.560	1.560	0.000
	100	27.70	27.70	0.00	2.170	2.170	0.000
POA-B Offsite - West	2	0.47	0.47	0.00	0.040	0.040	0.000
	10	0.91	0.91	0.00	0.075	0.075	0.000
	25	1.20	1.20	0.00	0.100	0.100	0.000
	100	1.65	1.65	0.00	0.138	0.138	0.000
POA-C Southeast Wetland	2	2.14	2.14	0.00	0.215	0.215	0.000
	10	4.20	4.20	0.00	0.415	0.415	0.000
	25	5.57	5.57	0.00	0.550	0.550	0.000
	100	7.70	7.70	0.00	0.765	0.765	0.000
POA-D Offsite - East	2	6.67	6.67	0.00	0.607	0.607	0.000
	10	12.20	12.20	0.00	1.111	1.111	0.000
	25	15.78	15.78	0.00	1.444	1.444	0.000
	100	21.29	21.29	0.00	1.968	1.968	0.000


### Conclusion

The proposed solar PV array located at the Town of Montville Landfill will include minor vegetation trimming within the array area, minor access road improvements, and the implementation of erosion and sediment controls. The analysis shows no change in peak discharge runoff rates for post-development conditions compared to pre-development conditions.

No stormwater management system is proposed as there is no increase in stormwater runoff rate or volume. Similarly, water quality volume calculations and treatment per the 2004 Connecticut Stormwater Quality Manual are not provided for this project.

Attachment A - Locus Map





**FIGURE 1**  
**TOWN OF MONTVILLE LANDFILL SOLAR PV DEVELOPMENT**  
**669 OAKDALE ROAD (CT RT 163), MONTVILLE, CT 06353**  
**VCP MONTVILLE LF, LLC**


**LOCUS MAP**






Attachment B - NRCS Web Soil Survey Map & Report: Hydrologic Soils Group,  
FEMA FIRMette,  
NOAA Atlas 14 Rainfall Data

# Hydrologic Soil Group—State of Connecticut



Map Scale: 1:2,940 if printed on A landscape (11" x 8.5") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 18N WGS84



**Natural Resources  
Conservation Service**

Web Soil Survey  
National Cooperative Soil Survey

4/18/2023  
Page 1 of 4

## MAP LEGEND

### Area of Interest (AOI)









Area of Interest (AOI)

### Soils

#### Soil Rating Polygons





-  A
-  A/D
-  B
-  B/D
-  C
-  C/D
-  D
-  Not rated or not available

#### Soil Rating Lines


-  A
-  A/D
-  B
-  B/D
-  C
-  C/D
-  D
-  Not rated or not available

#### Soil Rating Points






-  A
-  A/D
-  B
-  B/D

-  C
-  C/D
-  D
-  Not rated or not available

### Water Features

-  Streams and Canals

### Transportation

-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads

### Background

-  Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:12,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service  
Web Soil Survey URL:  
Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: State of Connecticut  
Survey Area Data: Version 22, Sep 12, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 14, 2022—Oct 6, 2022

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

## Hydrologic Soil Group

Map unit symbol	Map unit name	Rating	Acres in AOI	Percent of AOI
38C	Hinckley loamy sand, 3 to 15 percent slopes	A	0.9	3.5%
38E	Hinckley loamy sand, 15 to 45 percent slopes	A	3.6	14.0%
62C	Canton and Charlton fine sandy loams, 3 to 15 percent slopes, extremely stony	B	0.1	0.4%
102	Pootatuck fine sandy loam	B	0.3	1.1%
302	Dumps		8.9	34.9%
701A	Ninigret fine sandy loam, 0 to 3 percent slopes	C	0.7	2.8%
702A	Tisbury silt loam, 0 to 3 percent slopes	C	7.9	31.1%
703A	Haven silt loam, 0 to 3 percent slopes	B	2.2	8.8%
W	Water		0.8	3.3%
<b>Totals for Area of Interest</b>			<b>25.4</b>	<b>100.0%</b>



## Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

## Rating Options

*Aggregation Method:* Dominant Condition

*Component Percent Cutoff:* None Specified

*Tie-break Rule:* Higher



## POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Sandra Pavlovic, Michael St. Laurent, Carl Trypaluk, Dale Unruh, Orlan Wilhite

NOAA, National Weather Service, Silver Spring, Maryland

[PF\\_tabular](#) | [PF\\_graphical](#) | [Maps & aerals](#)

### PF tabular

PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches) <sup>1</sup>										
Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	0.340 (0.264-0.427)	0.406 (0.316-0.510)	0.515 (0.398-0.647)	0.605 (0.466-0.765)	0.729 (0.544-0.956)	0.822 (0.602-1.10)	0.920 (0.654-1.27)	1.03 (0.693-1.44)	1.19 (0.772-1.72)	1.32 (0.836-1.94)
10-min	0.481 (0.374-0.604)	0.575 (0.447-0.723)	0.729 (0.564-0.919)	0.856 (0.659-1.08)	1.03 (0.770-1.36)	1.16 (0.851-1.56)	1.30 (0.926-1.80)	1.46 (0.983-2.04)	1.69 (1.09-2.43)	1.87 (1.18-2.74)
15-min	0.566 (0.440-0.711)	0.677 (0.526-0.851)	0.858 (0.664-1.08)	1.01 (0.776-1.28)	1.21 (0.906-1.59)	1.37 (1.00-1.83)	1.53 (1.09-2.11)	1.72 (1.16-2.40)	1.98 (1.28-2.86)	2.20 (1.39-3.22)
30-min	0.795 (0.618-0.998)	0.950 (0.738-1.19)	1.20 (0.932-1.52)	1.41 (1.09-1.79)	1.70 (1.27-2.24)	1.92 (1.40-2.56)	2.15 (1.53-2.96)	2.41 (1.62-3.37)	2.78 (1.80-4.00)	3.08 (1.95-4.51)
60-min	1.02 (0.795-1.28)	1.22 (0.950-1.54)	1.55 (1.20-1.95)	1.82 (1.40-2.30)	2.19 (1.64-2.88)	2.47 (1.81-3.30)	2.77 (1.96-3.81)	3.10 (2.08-4.33)	3.57 (2.32-5.14)	3.96 (2.51-5.80)
2-hr	1.34 (1.05-1.68)	1.60 (1.25-2.00)	2.03 (1.58-2.54)	2.38 (1.84-2.99)	2.86 (2.15-3.73)	3.22 (2.37-4.28)	3.60 (2.58-4.94)	4.05 (2.74-5.62)	4.70 (3.06-6.71)	5.24 (3.33-7.61)
3-hr	1.56 (1.23-1.94)	1.86 (1.46-2.31)	2.35 (1.84-2.92)	2.75 (2.14-3.44)	3.31 (2.50-4.30)	3.72 (2.75-4.92)	4.16 (3.00-5.69)	4.68 (3.17-6.46)	5.44 (3.55-7.73)	6.09 (3.88-8.78)
6-hr	1.99 (1.58-2.45)	2.36 (1.87-2.92)	2.97 (2.34-3.68)	3.48 (2.72-4.32)	4.17 (3.17-5.38)	4.69 (3.49-6.16)	5.24 (3.80-7.11)	5.89 (4.01-8.07)	6.85 (4.49-9.64)	7.66 (4.90-11.0)
12-hr	2.46 (1.97-3.02)	2.92 (2.33-3.58)	3.67 (2.92-4.52)	4.30 (3.39-5.30)	5.15 (3.94-6.59)	5.79 (4.33-7.54)	6.47 (4.70-8.69)	7.26 (4.97-9.86)	8.42 (5.54-11.7)	9.39 (6.02-13.3)
24-hr	2.89 (2.32-3.52)	3.45 (2.77-4.20)	4.36 (3.49-5.33)	5.12 (4.07-6.28)	6.17 (4.74-7.84)	6.94 (5.23-8.98)	7.78 (5.69-10.4)	8.74 (6.01-11.8)	10.2 (6.72-14.1)	11.4 (7.33-16.0)
2-day	3.24 (2.62-3.92)	3.91 (3.16-4.73)	5.00 (4.03-6.07)	5.91 (4.73-7.20)	7.16 (5.55-9.05)	8.08 (6.14-10.4)	9.08 (6.70-12.1)	10.3 (7.10-13.7)	12.1 (8.00-16.5)	13.6 (8.80-18.9)
3-day	3.52 (2.86-4.24)	4.24 (3.45-5.12)	5.43 (4.39-6.56)	6.41 (5.16-7.78)	7.77 (6.04-9.77)	8.77 (6.68-11.2)	9.85 (7.30-13.0)	11.2 (7.73-14.8)	13.1 (8.72-17.9)	14.8 (9.60-20.5)
4-day	3.78 (3.08-4.54)	4.54 (3.70-5.46)	5.79 (4.70-6.98)	6.83 (5.51-8.25)	8.25 (6.44-10.3)	9.31 (7.11-11.9)	10.4 (7.76-13.8)	11.8 (8.20-15.6)	13.9 (9.24-18.8)	15.7 (10.2-21.6)
7-day	4.51 (3.70-5.38)	5.35 (4.38-6.39)	6.72 (5.49-8.05)	7.86 (6.37-9.44)	9.42 (7.39-11.7)	10.6 (8.12-13.4)	11.8 (8.81-15.4)	13.3 (9.28-17.5)	15.5 (10.4-20.9)	17.4 (11.3-23.8)
10-day	5.23 (4.31-6.22)	6.11 (5.03-7.28)	7.55 (6.19-9.01)	8.74 (7.12-10.5)	10.4 (8.16-12.8)	11.6 (8.93-14.6)	12.9 (9.61-16.7)	14.4 (10.1-18.8)	16.6 (11.2-22.3)	18.5 (12.1-25.1)
20-day	7.45 (6.18-8.80)	8.38 (6.95-9.91)	9.92 (8.19-11.8)	11.2 (9.18-13.3)	12.9 (10.2-15.8)	14.3 (11.0-17.7)	15.6 (11.6-19.8)	17.1 (12.0-22.1)	19.1 (12.8-25.2)	20.6 (13.5-27.7)
30-day	9.29 (7.75-10.9)	10.3 (8.55-12.1)	11.9 (9.83-14.0)	13.2 (10.9-15.6)	15.0 (11.9-18.2)	16.4 (12.6-20.1)	17.8 (13.2-22.2)	19.1 (13.5-24.6)	20.9 (14.1-27.5)	22.2 (14.6-29.7)
45-day	11.6 (9.69-13.6)	12.6 (10.5-14.8)	14.3 (11.9-16.7)	15.6 (12.9-18.4)	17.5 (13.9-21.1)	19.0 (14.7-23.2)	20.5 (15.1-25.3)	21.7 (15.4-27.8)	23.3 (15.8-30.5)	24.3 (16.0-32.4)
60-day	13.5 (11.3-15.7)	14.5 (12.2-17.0)	16.3 (13.6-19.1)	17.7 (14.7-20.8)	19.7 (15.7-23.6)	21.3 (16.5-25.8)	22.8 (16.8-28.0)	24.0 (17.1-30.5)	25.5 (17.3-33.2)	26.3 (17.4-34.9)


<sup>1</sup> Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).

Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Please refer to NOAA Atlas 14 document for more information.

Attachment C - Drainage Area Maps & HydroCAD Reports





Project:

TOWN OF MONTVILLE  
LANDFILL  
SOLAR PV DEVELOPMENT

669 ROUTE 163  
MONTVILLE, CT 06353

Veston & Sampson<sup>SM</sup>

WESTON & SAMPSON ENGINEERS, INC.  
712 BROOK STREET, SUITE 103  
ROCKY HILL, CT 06067  
860.513.1473 800.SAMPSON  
[www.westonandsampson.com](http://www.westonandsampson.com)

Applicant: \_\_\_\_\_

**VEROGY**

VCP MONTVILLE LF, LLC  
150 TRUMBULL STREET  
4TH FLOOR  
HARTFORD, CT 06103  
TEL: (860) 288-7215  
[WWW.VEROGY.COM](http://WWW.VEROGY.COM)

Revisions:		
0	06/06/2023	ISSUED FOR PERMITTING
No.	Date	Description

Seal:

Issued For:

PERMITTING

Scale: AS SHOWN

Date Created: 06/06/2023

Drawn By: NVG

Reviewed By: MRC

Approved By: RJB

W&S Project No.: ENG23-1066  
W&S File No.: Verogy Montville

Drawing Title:

## PRE- DEVELOPMENT DRAINAGE AREA MAP

Sheet Number:

FIG 2

COPYRIGHT © 2023 WESTON & SAMPSON, INC.



NOTES:

- BASEMAPPING DERIVED FROM SURVEY PROVIDED BY NORTHEAST SURVEY CONSULTANTS ENTITLED "PLAN OF LAND IN MONTVILLE, CT, 669 ROUTE 163, PREPARED FOR VEROGY" AND DATED 4-4-2023.
- SOIL DATA PROVIDED BY NATIONAL RESOURCE CONSERVATION SERVICE (NRCS) WEB SOIL SURVEY.
- SOIL GEOGRAPHIC INFORMATION SYSTEM (GIS) DATA DERIVED FROM CONNECTICUT DEPARTMENT OF ENERGY & ENVIRONMENTAL PROTECTION GIS OPEN DATA WEBSITE SOIL SURVEY GEOGRAPHIC DATABASE SOILS (SSURGO).
- HYDROLOGIC SOIL GROUP (HSG) D SOILS ASSUMED TO BE WITHIN THE FOOTPRINT OF THE LIMIT OF WASTE WHICH IS ASSUMED TO EXTEND TO LANDFILL TOE OF SLOPE.

LEGEND DRAINAGE AREA MAP:

HYDROLOGY:

- FLOW PATH / TIME OF CONCENTRATION
- SUBBASIN LABEL
- POINT OF ANALYSIS
- BASIN BMP
- MEADOW
- WOODLAND
- GRAVEL
- IMPERVIOUS
- WATERSHED BOUNDARY
- NRCS SOIL BOUNDARY
- ASSUMED HSG-D SOIL BOUNDARY
- NRCS SOIL MAP UNIT
- HYDROLOGIC SOIL GROUP A
- HYDROLOGIC SOIL GROUP B
- HYDROLOGIC SOIL GROUP C
- HYDROLOGIC SOIL GROUP D

PROPOSED LEGEND:

- LOW LOW LIMIT OF WORK
- SB SB SB SB SEDIMENT BARRIER
- x x x FENCE
- EC EC ELECTRIC CONDUIT
- OHE OHE OVERHEAD ELECTRIC
- SOLAR PV RACK
- UTILITY POLE
- ACCESS ROAD

EXISTING LEGEND:

- LOCUS PROPERTY LINE
- ABUTTERS PROPERTY LINE
- EASEMENT LINE
- 2" CONTOUR LINE
- CHAIN LINK FENCE
- WETLAND LINE
- 50' UPLAND REVIEW AREA
- TREE LINE
- TREE LINE
- FEMA FLOOD ZONE LINE
- ZONING LINE
- OVERHEAD WIRES
- BURIED GAS LINE
- BURIED DRAINAGE LINE
- NRCS SOIL MAP UNIT

- CONC. BOUND FOUND
- CALCULATED POINT
- UTILITY POLE
- LIGHT POLE
- GUY WIRE ANCHOR
- CATCH BASIN
- MANHOLE
- WETLAND FLAG WITH IDENTIFIER
- SIGN POST
- GAS VALVE
- CONCRETE PAD
- GRAVEL
- SAND AND GRAVEL
- PAVEMENT
- STRUCTURE

POST-DEVELOPMENT TC LIST					
Drainage Area	Flow Type	Ground Cover	Length (ft)	Slope	
A1	SHEET	MEADOW	100	11.00%	
	SCF	MEADOW	13	34.62%	
	SCF	GRAVEL	8	12.50%	
	SCF	MEADOW	21	30.95%	
	SCF	WOODS	166	25.30%	
B1	SHEET	MEADOW	100	5.00%	
	SCF	MEADOW	62	12.90%	
	SCF	MEADOW	51	33.33%	
	SCF	GRAVEL	10	10.00%	
	SCF	MEADOW	31	29.03%	
C1	SHEET	MEADOW	100	3.00%	
	SCF	MEADOW	126	7.94%	
	SCF	MEADOW	80	33.75%	
	SCF	PAVEMENT	607	2.64%	
	SCF	MEADOW	44	11.36%	
D1	SHEET	MEADOW	100	6.00%	
	SCF	MEADOW	73	17.81%	
	SCF	MEADOW	64	42.19%	
	SCF	PAVEMENT	634	3.94%	
	SCF	GRAVEL	94	0.53%	

Soil Data		
Map Unit Symbol	Map Unit Name	HSG Rating
38C	Hinckley loamy sand, 3 to 15 percent slopes	A
38E	Hinckley loamy sand, 15 to 45 percent slopes	A
62C	Canton and Charlton fine sandy loams, 3 to 15 percent slopes, extremely stony	B
302	Dumps	D
701A	Ninigret fine sandy loam, 0 to 3 percent slopes	C
702A	Tisbury silt loam, 0 to 3 percent slopes	C

50 25 0 50 100  
SCALE: 1"=50'

NOT FOR CONSTRUCTION

Project:  
TOWN OF MONTVILLE  
LANDFILL  
SOLAR PV DEVELOPMENT

669 ROUTE 163  
MONTVILLE, CT 06353

Weston & Sampson

WESTON & SAMPSON ENGINEERS, INC.  
712 BROOK STREET, SUITE 103  
ROCKY HILL, CT 06067  
860.513.1473 800.SAMPSON  
www.westonandsampson.com

Applicant:

VEROGY

VCP MONTVILLE, LLC  
150 TRUMBULL STREET  
4TH FLOOR  
HARTFORD, CT 06103  
TEL: (860) 288-7215  
WWW.VEROGY.COM

Revisions:

0	06/06/2023	ISSUED FOR PERMITTING
No.	Date	Description

Seal:

Issued For:

PERMITTING

Scale: AS SHOWN

Date Created: 06/06/2023

Drawn By: NVG

Reviewed By: MRC

Approved By: RJB

W&S Project No.: ENG23-1066

W&S File No.: Verogy Montville


Drawing Title:

POST-DEVELOPMENT  
DRAINAGE AREA MAP

Sheet Number:

FIG 3





### 669 Oakdale Road Montville - Pre

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Printed 6/12/2023

Page 2

#### Rainfall Events Listing

Event#	Event Name	Storm Type	Curve	Mode	Duration (hours)	B/B	Depth (inches)	AMC
1	2-yr	Type III 24-hr		Default	24.00	1	3.45	2
2	10-yr	Type III 24-hr		Default	24.00	1	5.12	2
3	25-yr	Type III 24-hr		Default	24.00	1	6.17	2
4	100-yr	Type III 24-hr		Default	24.00	1	7.78	2



**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Printed 6/12/2023

Page 3

**Area Listing (all nodes)**

Area (acres)	CN	Description (subcatchment-numbers)
0.231	76	Gravel roads, HSG A (D)
0.043	89	Gravel roads, HSG C (A, D)
0.432	91	Gravel roads, HSG D (A, B, C, D)
0.229	30	Meadow, non-grazed, HSG A (A, C, D)
0.114	71	Meadow, non-grazed, HSG C (A, C, D)
5.644	78	Meadow, non-grazed, HSG D (A, B, C, D)
0.357	98	Paved parking, HSG A (C, D)
0.014	98	Paved parking, HSG B (C)
0.008	98	Paved parking, HSG C (D)
0.819	98	Paved parking, HSG D (C, D)
0.023	36	Woods, Fair, HSG A (A, C)
0.842	73	Woods, Fair, HSG C (A, C)
2.528	79	Woods, Fair, HSG D (A, C, D)
<b>11.283</b>	<b>79</b>	<b>TOTAL AREA</b>

**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 4

**Summary for Subcatchment A:**

Runoff = 7.73 cfs @ 12.12 hrs, Volume= 0.610 af, Depth= 1.46"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.45"


Area (sf)	CN	Description
13,906	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
66,841	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
92,438	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
6,666	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
218,623	78	Weighted Average
218,623		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

## Subcatchment A:

## Hydrograph



## Summary for Subcatchment B:

Runoff = 0.47 cfs @ 12.15 hrs, Volume= 0.040 af, Depth= 1.53"  
Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.45"


Area (sf)	CN	Description
3,577	78	Meadow, non-grazed, HSG D
8,878	78	Meadow, non-grazed, HSG D
1,122	91	Gravel roads, HSG D
13,577	79	Weighted Average
13,577		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		Sheet Flow, Sheet - Meadow
					Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		Shallow Concentrated Flow, Shallow - Gravel
					Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B:

## Hydrograph



## Summary for Subcatchment C:

Runoff = 2.14 cfs @ 12.24 hrs, Volume= 0.215 af, Depth= 1.46"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.45"

Area (sf)	CN	Description
13,937	78	Meadow, non-grazed, HSG D
1,693	71	Meadow, non-grazed, HSG C
8,141	30	Meadow, non-grazed, HSG A
18,914	78	Meadow, non-grazed, HSG D
7,463	79	Woods, Fair, HSG D
2,986	73	Woods, Fair, HSG C
336	36	Woods, Fair, HSG A
2,453	91	Gravel roads, HSG D
8,413	98	Paved parking, HSG D
620	98	Paved parking, HSG B
12,143	98	Paved parking, HSG A
77,099	78	Weighted Average
55,923		72.53% Pervious Area
21,176		27.47% Impervious Area

**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 9

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 10

**Summary for Subcatchment D:**

Runoff = 6.67 cfs @ 12.19 hrs, Volume= 0.607 af, Depth= 1.74"  
 Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-yr Rainfall=3.45"

Area (sf)	CN	Description
38,983	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
80,797	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
10,224	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,558	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,271	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
182,194	82	Weighted Average
151,197		82.99% Pervious Area
30,997		17.01% Impervious Area

# 669 Oakdale Road Montville - Pre

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC


Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 11

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

## Subcatchment D:



# 669 Oakdale Road Montville - Pre

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023


Page 12

## Summary for Link POA-A:

Inflow Area = 5.019 ac, 0.00% Impervious, Inflow Depth = 1.46" for 2-yr event  
Inflow = 7.73 cfs @ 12.12 hrs, Volume= 0.610 af  
Primary = 7.73 cfs @ 12.12 hrs, Volume= 0.610 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-A:




## Summary for Link POA-B:

Inflow Area = 0.312 ac, 0.00% Impervious, Inflow Depth = 1.53" for 2-yr event  
Inflow = 0.47 cfs @ 12.15 hrs, Volume= 0.040 af  
Primary = 0.47 cfs @ 12.15 hrs, Volume= 0.040 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-B:

## Hydrograph




## Summary for Link POA-C:

Inflow Area = 1.770 ac, 27.47% Impervious, Inflow Depth = 1.46" for 2-yr event  
Inflow = 2.14 cfs @ 12.24 hrs, Volume= 0.215 af  
Primary = 2.14 cfs @ 12.24 hrs, Volume= 0.215 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-C:

## Hydrograph





**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"


Printed 6/12/2023

Page 15

**Summary for Link POA-D:**

Inflow Area = 4.183 ac, 17.01% Impervious, Inflow Depth = 1.74" for 2-yr event  
Inflow = 6.67 cfs @ 12.19 hrs, Volume= 0.607 af  
Primary = 6.67 cfs @ 12.19 hrs, Volume= 0.607 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-D:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 16

**Summary for Subcatchment A:**

Runoff = 15.14 cfs @ 12.12 hrs, Volume= 1.177 af, Depth= 2.81"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"


Area (sf)	CN	Description
13,906	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
66,841	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
92,438	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
6,666	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
218,623	78	Weighted Average
218,623		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

## Subcatchment A:

## Hydrograph



## Summary for Subcatchment B:

Runoff = 0.91 cfs @ 12.15 hrs, Volume= 0.075 af, Depth= 2.91"  
Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"


Area (sf)	CN	Description
3,577	78	Meadow, non-grazed, HSG D
8,878	78	Meadow, non-grazed, HSG D
1,122	91	Gravel roads, HSG D
13,577	79	Weighted Average
13,577		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		Sheet Flow, Sheet - Meadow
					Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		Shallow Concentrated Flow, Shallow - Gravel
					Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B:

## Hydrograph



## Summary for Subcatchment C:

Runoff = 4.20 cfs @ 12.23 hrs, Volume= 0.415 af, Depth= 2.81"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"

Area (sf)	CN	Description
13,937	78	Meadow, non-grazed, HSG D
1,693	71	Meadow, non-grazed, HSG C
8,141	30	Meadow, non-grazed, HSG A
18,914	78	Meadow, non-grazed, HSG D
7,463	79	Woods, Fair, HSG D
2,986	73	Woods, Fair, HSG C
336	36	Woods, Fair, HSG A
2,453	91	Gravel roads, HSG D
8,413	98	Paved parking, HSG D
620	98	Paved parking, HSG B
12,143	98	Paved parking, HSG A
77,099	78	Weighted Average
55,923		72.53% Pervious Area
21,176		27.47% Impervious Area

**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 21

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 22

**Summary for Subcatchment D:**

Runoff = 12.20 cfs @ 12.19 hrs, Volume= 1.111 af, Depth= 3.19"  
Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"

Area (sf)	CN	Description
38,983	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
80,797	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
10,224	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,558	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,271	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
182,194	82	Weighted Average
151,197		82.99% Pervious Area
30,997		17.01% Impervious Area

**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 23

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"


Printed 6/12/2023

Page 24

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.00% Impervious, Inflow Depth = 2.81" for 10-yr event  
Inflow = 15.14 cfs @ 12.12 hrs, Volume= 1.177 af  
Primary = 15.14 cfs @ 12.12 hrs, Volume= 1.177 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**


## Summary for Link POA-B:

Inflow Area = 0.312 ac, 0.00% Impervious, Inflow Depth = 2.91" for 10-yr event  
Inflow = 0.91 cfs @ 12.15 hrs, Volume= 0.075 af  
Primary = 0.91 cfs @ 12.15 hrs, Volume= 0.075 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-B:

Hydrograph




## Summary for Link POA-C:

Inflow Area = 1.770 ac, 27.47% Impervious, Inflow Depth = 2.81" for 10-yr event  
Inflow = 4.20 cfs @ 12.23 hrs, Volume= 0.415 af  
Primary = 4.20 cfs @ 12.23 hrs, Volume= 0.415 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-C:

Hydrograph





**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 27


**Summary for Link POA-D:**

Inflow Area = 4.183 ac, 17.01% Impervious, Inflow Depth = 3.19" for 10-yr event  
Inflow = 12.20 cfs @ 12.19 hrs, Volume= 1.111 af  
Primary = 12.20 cfs @ 12.19 hrs, Volume= 1.111 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-D:**

Hydrograph

**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 28

**Summary for Subcatchment A:**

Runoff = 20.05 cfs @ 12.12 hrs, Volume= 1.560 af, Depth= 3.73"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"


Area (sf)	CN	Description
13,906	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
66,841	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
92,438	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
6,666	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
218,623	78	Weighted Average
218,623		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

## Subcatchment A:

## Hydrograph



## Summary for Subcatchment B:

Runoff = 1.20 cfs @ 12.15 hrs, Volume= 0.100 af, Depth= 3.83"  
Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"


Area (sf)	CN	Description
3,577	78	Meadow, non-grazed, HSG D
8,878	78	Meadow, non-grazed, HSG D
1,122	91	Gravel roads, HSG D
13,577	79	Weighted Average
13,577		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		Sheet Flow, Sheet - Meadow
					Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		Shallow Concentrated Flow, Shallow - Gravel
					Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B:

## Hydrograph



## Summary for Subcatchment C:

Runoff = 5.57 cfs @ 12.23 hrs, Volume= 0.550 af, Depth= 3.73"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"

Area (sf)	CN	Description
13,937	78	Meadow, non-grazed, HSG D
1,693	71	Meadow, non-grazed, HSG C
8,141	30	Meadow, non-grazed, HSG A
18,914	78	Meadow, non-grazed, HSG D
7,463	79	Woods, Fair, HSG D
2,986	73	Woods, Fair, HSG C
336	36	Woods, Fair, HSG A
2,453	91	Gravel roads, HSG D
8,413	98	Paved parking, HSG D
620	98	Paved parking, HSG B
12,143	98	Paved parking, HSG A
77,099	78	Weighted Average
55,923		72.53% Pervious Area
21,176		27.47% Impervious Area

**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 33

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 34

**Summary for Subcatchment D:**

Runoff = 15.78 cfs @ 12.18 hrs, Volume= 1.444 af, Depth= 4.14"  
Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"

Area (sf)	CN	Description
38,983	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
80,797	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
10,224	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,558	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,271	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
182,194	82	Weighted Average
151,197		82.99% Pervious Area
30,997		17.01% Impervious Area

**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

*Type III 24-hr 25-yr Rainfall=6.17"*

Printed 6/12/2023

Page 35

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

*Type III 24-hr 25-yr Rainfall=6.17"*


Printed 6/12/2023

Page 36

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.00% Impervious, Inflow Depth = 3.73" for 25-yr event  
Inflow = 20.05 cfs @ 12.12 hrs, Volume= 1.560 af  
Primary = 20.05 cfs @ 12.12 hrs, Volume= 1.560 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**




## Summary for Link POA-B:

Inflow Area = 0.312 ac, 0.00% Impervious, Inflow Depth = 3.83" for 25-yr event  
Inflow = 1.20 cfs @ 12.15 hrs, Volume= 0.100 af  
Primary = 1.20 cfs @ 12.15 hrs, Volume= 0.100 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-B:

## Hydrograph




## Summary for Link POA-C:

Inflow Area = 1.770 ac, 27.47% Impervious, Inflow Depth = 3.73" for 25-yr event  
Inflow = 5.57 cfs @ 12.23 hrs, Volume= 0.550 af  
Primary = 5.57 cfs @ 12.23 hrs, Volume= 0.550 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-C:

## Hydrograph



**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 39


**Summary for Link POA-D:**

Inflow Area = 4.183 ac, 17.01% Impervious, Inflow Depth = 4.14" for 25-yr event  
Inflow = 15.78 cfs @ 12.18 hrs, Volume= 1.444 af  
Primary = 15.78 cfs @ 12.18 hrs, Volume= 1.444 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-D:**

Hydrograph

**669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 40

**Summary for Subcatchment A:**

Runoff = 27.70 cfs @ 12.12 hrs, Volume= 2.170 af, Depth= 5.19"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-yr Rainfall=7.78"


Area (sf)	CN	Description
13,906	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
66,841	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
92,438	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
6,666	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
218,623	78	Weighted Average
218,623		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

## Subcatchment A:

## Hydrograph



## Summary for Subcatchment B:

Runoff = 1.65 cfs @ 12.14 hrs, Volume= 0.138 af, Depth= 5.30"  
Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-yr Rainfall=7.78"


Area (sf)	CN	Description
3,577	78	Meadow, non-grazed, HSG D
8,878	78	Meadow, non-grazed, HSG D
1,122	91	Gravel roads, HSG D
13,577	79	Weighted Average
13,577		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		Sheet Flow, Sheet - Meadow
					Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		Shallow Concentrated Flow, Shallow - Gravel
					Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		Shallow Concentrated Flow, Shallow - Meadow
					Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B:

## Hydrograph



## Summary for Subcatchment C:

Runoff = 7.70 cfs @ 12.23 hrs, Volume= 0.765 af, Depth= 5.19"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-yr Rainfall=7.78"

Area (sf)	CN	Description
13,937	78	Meadow, non-grazed, HSG D
1,693	71	Meadow, non-grazed, HSG C
8,141	30	Meadow, non-grazed, HSG A
18,914	78	Meadow, non-grazed, HSG D
7,463	79	Woods, Fair, HSG D
2,986	73	Woods, Fair, HSG C
336	36	Woods, Fair, HSG A
2,453	91	Gravel roads, HSG D
8,413	98	Paved parking, HSG D
620	98	Paved parking, HSG B
12,143	98	Paved parking, HSG A
77,099	78	Weighted Average
55,923		72.53% Pervious Area
21,176		27.47% Impervious Area

**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 45

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 46

**Summary for Subcatchment D:**

Runoff = 21.29 cfs @ 12.18 hrs, Volume= 1.968 af, Depth= 5.65"  
Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-yr Rainfall=7.78"

Area (sf)	CN	Description
38,983	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
80,797	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
10,224	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,558	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,271	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
182,194	82	Weighted Average
151,197		82.99% Pervious Area
30,997		17.01% Impervious Area



**669 Oakdale Road Montville - Pre**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 47

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D:****669 Oakdale Road Montville - Pre**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"


Printed 6/12/2023

Page 48

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.00% Impervious, Inflow Depth = 5.19" for 100-yr event  
Inflow = 27.70 cfs @ 12.12 hrs, Volume= 2.170 af  
Primary = 27.70 cfs @ 12.12 hrs, Volume= 2.170 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**


## Summary for Link POA-B:

Inflow Area = 0.312 ac, 0.00% Impervious, Inflow Depth > 5.30" for 100-yr event  
Inflow = 1.65 cfs @ 12.14 hrs, Volume= 0.138 af  
Primary = 1.65 cfs @ 12.14 hrs, Volume= 0.138 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-B:

## Hydrograph




## Summary for Link POA-C:

Inflow Area = 1.770 ac, 27.47% Impervious, Inflow Depth = 5.19" for 100-yr event  
Inflow = 7.70 cfs @ 12.23 hrs, Volume= 0.765 af  
Primary = 7.70 cfs @ 12.23 hrs, Volume= 0.765 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-C:

## Hydrograph




## Summary for Link POA-D:


Inflow Area = 4.183 ac, 17.01% Impervious, Inflow Depth > 5.65" for 100-yr event  
Inflow = 21.29 cfs @ 12.18 hrs, Volume= 1.968 af  
Primary = 21.29 cfs @ 12.18 hrs, Volume= 1.968 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-D:

Hydrograph





### 669 Oakdale Road Montville - Post

Prepared by Weston & Sampson Engineers, Inc.  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Printed 6/12/2023

Page 2

#### Rainfall Events Listing

Event#	Event Name	Storm Type	Curve	Mode	Duration (hours)	B/B	Depth (inches)	AMC
1	2-yr	Type III 24-hr		Default	24.00	1	3.45	2
2	10-yr	Type III 24-hr		Default	24.00	1	5.12	2
3	25-yr	Type III 24-hr		Default	24.00	1	6.17	2
4	100-yr	Type III 24-hr		Default	24.00	1	7.78	2

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Printed 6/12/2023

Page 3

**Area Listing (all nodes)**

Area (acres)	CN	Description (subcatchment-numbers)
0.231	76	Gravel roads, HSG A (D1)
0.043	89	Gravel roads, HSG C (A1, D1)
0.446	91	Gravel roads, HSG D (A1, B1, C1, D1)
0.229	30	Meadow, non-grazed, HSG A (A1, C1, D1)
0.114	71	Meadow, non-grazed, HSG C (A1, C1, D1)
5.556	78	Meadow, non-grazed, HSG D (A1, B1, C1, D1)
0.357	98	Paved parking, HSG A (C1, D1)
0.014	98	Paved parking, HSG B (C1)
0.008	98	Paved parking, HSG C (D1)
0.832	98	Paved parking, HSG D (C1, D1)
0.092	98	Unconnected pavement, HSG D (A1, B1, C1, D1)
0.023	36	Woods, Fair, HSG A (A1, C1)
0.842	73	Woods, Fair, HSG C (A1, C1)
2.496	79	Woods, Fair, HSG D (A1, C1, D1)
<b>11.283</b>	<b>80</b>	<b>TOTAL AREA</b>

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 4

**Summary for Subcatchment A1:**

Runoff = 7.73 cfs @ 12.12 hrs, Volume= 0.610 af, Depth= 1.46"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.45"

Area (sf)	CN	Description
54,384	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
24,778	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
91,474	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
7,640	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
1,575	98	Unconnected pavement, HSG D
218,623	78	Weighted Average
217,048		99.28% Pervious Area
1,575		0.72% Impervious Area
1,575		100.00% Unconnected



**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 5

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

**Subcatchment A1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 6

**Summary for Subcatchment B1:**

Runoff = 0.47 cfs @ 12.15 hrs, Volume= 0.040 af, Depth= 1.53"  
 Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-yr Rainfall=3.45"


Area (sf)	CN	Description
6,112	78	Meadow, non-grazed, HSG D
6,218	78	Meadow, non-grazed, HSG D
1,112	91	Gravel roads, HSG D
135	98	Unconnected pavement, HSG D
13,577	79	Weighted Average
13,442		99.01% Pervious Area
135		0.99% Impervious Area
135		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B1:

## Hydrograph



## Summary for Subcatchment C1:

Runoff = 2.14 cfs @ 12.24 hrs, Volume= 0.215 af, Depth= 1.46"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 2-yr Rainfall=3.45"

Area (sf)	CN	Adj	Description
25,170	78		Meadow, non-grazed, HSG D
1,693	71		Meadow, non-grazed, HSG C
8,141	30		Meadow, non-grazed, HSG A
7,191	78		Meadow, non-grazed, HSG D
7,463	79		Woods, Fair, HSG D
2,986	73		Woods, Fair, HSG C
336	36		Woods, Fair, HSG A
2,358	91		Gravel roads, HSG D
8,413	98		Paved parking, HSG D
620	98		Paved parking, HSG B
12,143	98		Paved parking, HSG A
585	98		Unconnected pavement, HSG D
77,099	79	78	Weighted Average, UI Adjusted
55,338			71.78% Pervious Area
21,761			28.22% Impervious Area
585			2.69% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 9

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 10

**Summary for Subcatchment D1:**

Runoff = 6.67 cfs @ 12.19 hrs, Volume= 0.607 af, Depth= 1.74"  
 Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 2-yr Rainfall=3.45"

Area (sf)	CN	Description
80,169	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
38,003	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
9,808	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,312	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,831	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
1,710	98	Unconnected pavement, HSG D
182,194	82	Weighted Average
148,927		81.74% Pervious Area
33,267		18.26% Impervious Area
1,710		5.14% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"

Printed 6/12/2023

Page 11

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"


Printed 6/12/2023

Page 12

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.72% Impervious, Inflow Depth = 1.46" for 2-yr event  
Inflow = 7.73 cfs @ 12.12 hrs, Volume= 0.610 af  
Primary = 7.73 cfs @ 12.12 hrs, Volume= 0.610 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"


Printed 6/12/2023

Page 13

**Summary for Link POA-B:**

Inflow Area = 0.312 ac, 0.99% Impervious, Inflow Depth = 1.53" for 2-yr event  
Inflow = 0.47 cfs @ 12.15 hrs, Volume= 0.040 af  
Primary = 0.47 cfs @ 12.15 hrs, Volume= 0.040 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-B:****Hydrograph****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"


Printed 6/12/2023

Page 14

**Summary for Link POA-C:**

Inflow Area = 1.770 ac, 28.22% Impervious, Inflow Depth = 1.46" for 2-yr event  
Inflow = 2.14 cfs @ 12.24 hrs, Volume= 0.215 af  
Primary = 2.14 cfs @ 12.24 hrs, Volume= 0.215 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-C:****Hydrograph**

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 2-yr Rainfall=3.45"


Printed 6/12/2023

Page 15

**Summary for Link POA-D:**

Inflow Area = 4.183 ac, 18.26% Impervious, Inflow Depth = 1.74" for 2-yr event  
Inflow = 6.67 cfs @ 12.19 hrs, Volume= 0.607 af  
Primary = 6.67 cfs @ 12.19 hrs, Volume= 0.607 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-D:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 16

**Summary for Subcatchment A1:**

Runoff = 15.14 cfs @ 12.12 hrs, Volume= 1.177 af, Depth= 2.81"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"

Area (sf)	CN	Description
54,384	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
24,778	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
91,474	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
7,640	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
1,575	98	Unconnected pavement, HSG D
218,623	78	Weighted Average
217,048		99.28% Pervious Area
1,575		0.72% Impervious Area
1,575		100.00% Unconnected



**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 17

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

**Subcatchment A1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 18

**Summary for Subcatchment B1:**

Runoff = 0.91 cfs @ 12.15 hrs, Volume= 0.075 af, Depth= 2.91"  
Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"


Area (sf)	CN	Description
6,112	78	Meadow, non-grazed, HSG D
6,218	78	Meadow, non-grazed, HSG D
1,112	91	Gravel roads, HSG D
135	98	Unconnected pavement, HSG D
13,577	79	Weighted Average
13,442		99.01% Pervious Area
135		0.99% Impervious Area
135		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B1:

## Hydrograph



## Summary for Subcatchment C1:

Runoff = 4.20 cfs @ 12.23 hrs, Volume= 0.415 af, Depth= 2.81"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 10-yr Rainfall=5.12"

Area (sf)	CN	Adj	Description
25,170	78		Meadow, non-grazed, HSG D
1,693	71		Meadow, non-grazed, HSG C
8,141	30		Meadow, non-grazed, HSG A
7,191	78		Meadow, non-grazed, HSG D
7,463	79		Woods, Fair, HSG D
2,986	73		Woods, Fair, HSG C
336	36		Woods, Fair, HSG A
2,358	91		Gravel roads, HSG D
8,413	98		Paved parking, HSG D
620	98		Paved parking, HSG B
12,143	98		Paved parking, HSG A
585	98		Unconnected pavement, HSG D
77,099	79	78	Weighted Average, UI Adjusted
55,338			71.78% Pervious Area
21,761			28.22% Impervious Area
585			2.69% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 21

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 22

**Summary for Subcatchment D1:**

Runoff = 12.20 cfs @ 12.19 hrs, Volume= 1.111 af, Depth= 3.19"  
 Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 10-yr Rainfall=5.12"

Area (sf)	CN	Description
80,169	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
38,003	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
9,808	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,312	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,831	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
1,710	98	Unconnected pavement, HSG D
182,194	82	Weighted Average
148,927		81.74% Pervious Area
33,267		18.26% Impervious Area
1,710		5.14% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 23

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"


Printed 6/12/2023

Page 24

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.72% Impervious, Inflow Depth = 2.81" for 10-yr event  
Inflow = 15.14 cfs @ 12.12 hrs, Volume= 1.177 af  
Primary = 15.14 cfs @ 12.12 hrs, Volume= 1.177 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**


## Summary for Link POA-B:

Inflow Area = 0.312 ac, 0.99% Impervious, Inflow Depth = 2.91" for 10-yr event  
Inflow = 0.91 cfs @ 12.15 hrs, Volume= 0.075 af  
Primary = 0.91 cfs @ 12.15 hrs, Volume= 0.075 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-B:

## Hydrograph




## Summary for Link POA-C:

Inflow Area = 1.770 ac, 28.22% Impervious, Inflow Depth = 2.81" for 10-yr event  
Inflow = 4.20 cfs @ 12.23 hrs, Volume= 0.415 af  
Primary = 4.20 cfs @ 12.23 hrs, Volume= 0.415 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-C:

## Hydrograph



**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 10-yr Rainfall=5.12"

Printed 6/12/2023

Page 27


**Summary for Link POA-D:**

Inflow Area = 4.183 ac, 18.26% Impervious, Inflow Depth = 3.19" for 10-yr event  
Inflow = 12.20 cfs @ 12.19 hrs, Volume= 1.111 af  
Primary = 12.20 cfs @ 12.19 hrs, Volume= 1.111 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-D:**

Hydrograph

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 28

**Summary for Subcatchment A1:**

Runoff = 20.05 cfs @ 12.12 hrs, Volume= 1.560 af, Depth= 3.73"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"

Area (sf)	CN	Description
54,384	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
24,778	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
91,474	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
7,640	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
1,575	98	Unconnected pavement, HSG D
218,623	78	Weighted Average
217,048		99.28% Pervious Area
1,575		0.72% Impervious Area
1,575		100.00% Unconnected



**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 29

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

**Subcatchment A1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 30

**Summary for Subcatchment B1:**

Runoff = 1.20 cfs @ 12.15 hrs, Volume= 0.100 af, Depth= 3.83"  
Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"


Area (sf)	CN	Description
6,112	78	Meadow, non-grazed, HSG D
6,218	78	Meadow, non-grazed, HSG D
1,112	91	Gravel roads, HSG D
135	98	Unconnected pavement, HSG D
13,577	79	Weighted Average
13,442		99.01% Pervious Area
135		0.99% Impervious Area
135		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B1:

## Hydrograph



## Summary for Subcatchment C1:

Runoff = 5.57 cfs @ 12.23 hrs, Volume= 0.550 af, Depth= 3.73"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 25-yr Rainfall=6.17"

Area (sf)	CN	Adj	Description
25,170	78		Meadow, non-grazed, HSG D
1,693	71		Meadow, non-grazed, HSG C
8,141	30		Meadow, non-grazed, HSG A
7,191	78		Meadow, non-grazed, HSG D
7,463	79		Woods, Fair, HSG D
2,986	73		Woods, Fair, HSG C
336	36		Woods, Fair, HSG A
2,358	91		Gravel roads, HSG D
8,413	98		Paved parking, HSG D
620	98		Paved parking, HSG B
12,143	98		Paved parking, HSG A
585	98		Unconnected pavement, HSG D
77,099	79	78	Weighted Average, UI Adjusted
55,338			71.78% Pervious Area
21,761			28.22% Impervious Area
585			2.69% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 33

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 34

**Summary for Subcatchment D1:**

Runoff = 15.78 cfs @ 12.18 hrs, Volume= 1.444 af, Depth= 4.14"  
 Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 25-yr Rainfall=6.17"

Area (sf)	CN	Description
80,169	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
38,003	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
9,808	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,312	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,831	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
1,710	98	Unconnected pavement, HSG D
182,194	82	Weighted Average
148,927		81.74% Pervious Area
33,267		18.26% Impervious Area
1,710		5.14% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

*Type III 24-hr 25-yr Rainfall=6.17"*

Printed 6/12/2023

Page 35

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

*Type III 24-hr 25-yr Rainfall=6.17"*


Printed 6/12/2023

Page 36

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.72% Impervious, Inflow Depth = 3.73" for 25-yr event  
Inflow = 20.05 cfs @ 12.12 hrs, Volume= 1.560 af  
Primary = 20.05 cfs @ 12.12 hrs, Volume= 1.560 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**


## Summary for Link POA-B:

Inflow Area = 0.312 ac, 0.99% Impervious, Inflow Depth = 3.83" for 25-yr event  
Inflow = 1.20 cfs @ 12.15 hrs, Volume= 0.100 af  
Primary = 1.20 cfs @ 12.15 hrs, Volume= 0.100 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-B:

## Hydrograph




## Summary for Link POA-C:

Inflow Area = 1.770 ac, 28.22% Impervious, Inflow Depth = 3.73" for 25-yr event  
Inflow = 5.57 cfs @ 12.23 hrs, Volume= 0.550 af  
Primary = 5.57 cfs @ 12.23 hrs, Volume= 0.550 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-C:

## Hydrograph



**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 25-yr Rainfall=6.17"

Printed 6/12/2023

Page 39


**Summary for Link POA-D:**

Inflow Area = 4.183 ac, 18.26% Impervious, Inflow Depth = 4.14" for 25-yr event  
Inflow = 15.78 cfs @ 12.18 hrs, Volume= 1.444 af  
Primary = 15.78 cfs @ 12.18 hrs, Volume= 1.444 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-D:**

Hydrograph

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 40

**Summary for Subcatchment A1:**

Runoff = 27.70 cfs @ 12.12 hrs, Volume= 2.170 af, Depth= 5.19"  
Routed to Link POA-A :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-yr Rainfall=7.78"

Area (sf)	CN	Description
54,384	78	Meadow, non-grazed, HSG D
1,075	71	Meadow, non-grazed, HSG C
670	30	Meadow, non-grazed, HSG A
24,778	78	Meadow, non-grazed, HSG D
1,720	71	Meadow, non-grazed, HSG C
91,474	79	Woods, Fair, HSG D
33,692	73	Woods, Fair, HSG C
662	36	Woods, Fair, HSG A
7,640	91	Gravel roads, HSG D
953	89	Gravel roads, HSG C
1,575	98	Unconnected pavement, HSG D
218,623	78	Weighted Average
217,048		99.28% Pervious Area
1,575		0.72% Impervious Area
1,575		100.00% Unconnected



**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 41

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
6.9	100	0.1100	0.24		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.1	13	0.3462	4.12		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	8	0.1250	5.69		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	21	0.3095	3.89		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
1.1	166	0.2530	2.51		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
8.2	308	Total			

**Subcatchment A1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 42

**Summary for Subcatchment B1:**

Runoff = 1.65 cfs @ 12.14 hrs, Volume= 0.138 af, Depth= 5.30"  
 Routed to Link POA-B :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-yr Rainfall=7.78"


Area (sf)	CN	Description
6,112	78	Meadow, non-grazed, HSG D
6,218	78	Meadow, non-grazed, HSG D
1,112	91	Gravel roads, HSG D
135	98	Unconnected pavement, HSG D
13,577	79	Weighted Average
13,442		99.01% Pervious Area
135		0.99% Impervious Area
135		100.00% Unconnected

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.5	100	0.0500	0.17		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	62	0.1290	2.51		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	51	0.3333	4.04		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.0	10	0.1000	5.09		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
0.1	31	0.2903	3.77		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
10.2	254	Total			

## Subcatchment B1:

## Hydrograph



## Summary for Subcatchment C1:

Runoff = 7.70 cfs @ 12.23 hrs, Volume= 0.765 af, Depth= 5.19"  
Routed to Link POA-C :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
Type III 24-hr 100-yr Rainfall=7.78"

Area (sf)	CN	Adj	Description
25,170	78		Meadow, non-grazed, HSG D
1,693	71		Meadow, non-grazed, HSG C
8,141	30		Meadow, non-grazed, HSG A
7,191	78		Meadow, non-grazed, HSG D
7,463	79		Woods, Fair, HSG D
2,986	73		Woods, Fair, HSG C
336	36		Woods, Fair, HSG A
2,358	91		Gravel roads, HSG D
8,413	98		Paved parking, HSG D
620	98		Paved parking, HSG B
12,143	98		Paved parking, HSG A
585	98		Unconnected pavement, HSG D
77,099	79	78	Weighted Average, UI Adjusted
55,338			71.78% Pervious Area
21,761			28.22% Impervious Area
585			2.69% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 45

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.7	100	0.0300	0.14		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
1.1	126	0.0794	1.97		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	80	0.3375	4.07		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
3.1	607	0.0264	3.30		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
0.3	44	0.1136	2.36		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.3	44	0.2500	2.50		<b>Shallow Concentrated Flow, Shallow - Woods</b> Woodland Kv= 5.0 fps
16.8	1,001	Total			

**Subcatchment C1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
 HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 46

**Summary for Subcatchment D1:**

Runoff = 21.29 cfs @ 12.18 hrs, Volume= 1.968 af, Depth= 5.65"  
 Routed to Link POA-D :

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs  
 Type III 24-hr 100-yr Rainfall=7.78"

Area (sf)	CN	Description
80,169	78	Meadow, non-grazed, HSG D
0	71	Meadow, non-grazed, HSG C
1,146	30	Meadow, non-grazed, HSG A
38,003	78	Meadow, non-grazed, HSG D
489	71	Meadow, non-grazed, HSG C
9,808	79	Woods, Fair, HSG D
0	73	Woods, Fair, HSG C
8,312	91	Gravel roads, HSG D
940	89	Gravel roads, HSG C
10,060	76	Gravel roads, HSG A
27,831	98	Paved parking, HSG D
329	98	Paved parking, HSG C
3,397	98	Paved parking, HSG A
1,710	98	Unconnected pavement, HSG D
182,194	82	Weighted Average
148,927		81.74% Pervious Area
33,267		18.26% Impervious Area
1,710		5.14% Unconnected

**669 Oakdale Road Montville - Post**


Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 47

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.9	100	0.0600	0.19		<b>Sheet Flow, Sheet - Meadow</b> Grass: Dense n= 0.240 P2= 3.45"
0.4	73	0.1781	2.95		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
0.2	64	0.4219	4.55		<b>Shallow Concentrated Flow, Shallow - Meadow</b> Short Grass Pasture Kv= 7.0 fps
2.6	634	0.0394	4.03		<b>Shallow Concentrated Flow, Shallow - Pavement</b> Paved Kv= 20.3 fps
1.3	94	0.0053	1.17		<b>Shallow Concentrated Flow, Shallow - Gravel</b> Unpaved Kv= 16.1 fps
13.4	965	Total			

**Subcatchment D1:****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"


Printed 6/12/2023

Page 48

**Summary for Link POA-A:**

Inflow Area = 5.019 ac, 0.72% Impervious, Inflow Depth = 5.19" for 100-yr event  
Inflow = 27.70 cfs @ 12.12 hrs, Volume= 2.170 af  
Primary = 27.70 cfs @ 12.12 hrs, Volume= 2.170 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-A:**

**669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"


Printed 6/12/2023

Page 49

**Summary for Link POA-B:**

Inflow Area = 0.312 ac, 0.99% Impervious, Inflow Depth > 5.30" for 100-yr event  
Inflow = 1.65 cfs @ 12.14 hrs, Volume= 0.138 af  
Primary = 1.65 cfs @ 12.14 hrs, Volume= 0.138 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-B:****Hydrograph****669 Oakdale Road Montville - Post**

Prepared by Weston & Sampson Engineers, Inc  
HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"


Printed 6/12/2023

Page 50

**Summary for Link POA-C:**

Inflow Area = 1.770 ac, 28.22% Impervious, Inflow Depth = 5.19" for 100-yr event  
Inflow = 7.70 cfs @ 12.23 hrs, Volume= 0.765 af  
Primary = 7.70 cfs @ 12.23 hrs, Volume= 0.765 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

**Link POA-C:****Hydrograph**

# 669 Oakdale Road Montville - Post

Prepared by Weston & Sampson Engineers, Inc

HydroCAD® 10.20-2d s/n 00455 © 2021 HydroCAD Software Solutions LLC

Type III 24-hr 100-yr Rainfall=7.78"

Printed 6/12/2023

Page 51


## Summary for Link POA-D:

Inflow Area = 4.183 ac, 18.26% Impervious, Inflow Depth > 5.65" for 100-yr event  
Inflow = 21.29 cfs @ 12.18 hrs, Volume= 1.968 af  
Primary = 21.29 cfs @ 12.18 hrs, Volume= 1.968 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 6.00-30.00 hrs, dt= 0.05 hrs

## Link POA-D:

Hydrograph



# Authorization Application for Disruption of a Solid Waste Disposal Area

## APPENDIX G

### Draft Health and Safety Plan



# Site Specific Health and Safety Plan

For:

Montville Landfill Solar PV Development  
669 Oakdale Road  
Montville, Connecticut

Prepared By:



Weston & Sampson Engineers, Inc.  
55 Walkers Brook Drive  
Reading, Massachusetts

June 2023

## TABLE OF CONTENTS

	Page
1. Introduction .....	1
2. Description of Work .....	1
3. Project Organization .....	1
4. Project Staff .....	2
5. Hazard Evaluation and Control .....	2
6. Site Hazards .....	2
7. Communication Methods .....	5
8. Personal Protective Equipment .....	5
9. Environmental Monitoring .....	6
10. Training and Medical Surveillance .....	8
a. Training .....	8
b. Medical Surveillance .....	8
11. Site Control Measures .....	8
a. General Control Measures .....	8
b. Safety Briefings .....	9
c. Worksite Set Up .....	9
12. Emergency Response .....	9
a. Pre-Planning Activities .....	9
b. Evacuation Procedures .....	10
c. Medical Emergencies .....	11
d. Accident/Incident Reports .....	11
13. Plan Approval .....	11

### Tables:

Table 1. Hazardous Chemicals

Table 2. Physical Hazards

Table 3. Point of Operation and Operator Breathing Zone

Table 4. LEL Measurements

### Figures:

Figure 1. Emergency Evacuation Muster Locations

### Appendices:

Appendix A – Emergency Contact Information and Procedures

Appendix B – Employee HASP Review Signature Sheet

Appendix C – Daily Tailgate Meeting Form

Appendix D – Air Monitoring Log Sheet

## 1. Introduction

This Health and Safety Plan (HASP) has been prepared for construction oversight activities to be performed by Weston & Sampson Engineers, Inc. (Weston & Sampson) at Montville Landfill located at 669 Oakdale Road in Montville, Connecticut (the Site). The Landfill site consists of an approximately 29.09-acre lot of land on which the Town's transfer station is also operated. The Montville landfill was capped in the 1990s with 18 inches of impervious soil overlain by 6 inches of vegetated topsoil.

Site activities will consist of the construction of the Solar Photovoltaic (PV) Array (the Project) being performed by Verogy. The HASP has been prepared in response to hazardous conditions likely to be encountered at the Site. This HASP will be reviewed by Weston & Sampson employees working on this project, and a copy will be kept onsite during field activities associated with the Project.

## 2. Description of Work

Weston & Sampson will oversee the daily construction of an approximately 770 kilowatt (KW) direct current (DC) solar PV facility. Work that will be performed by Verogy and their subcontractors includes installation of temporary erosion and sedimentation controls, construction of a gravel turnaround area, setting of concrete ballast support blocks, conduit routing, installation of an electrical equipment pad, fence modifications and installation, and other tasks related to the construction of the solar PV array. Weston & Sampson will be onsite daily during land disturbance activities to monitor Verogy and their subcontractors for compliance with the requirements of the Connecticut Department of Energy and Environmental Protection (CT DEEP) Authorization Application for Disruption of a Solid Waste Disposal Area and local permit approval conditions. Periodic monitoring of landfill gas conditions will be performed daily, using a hand-held portable four-gas meter, for hydrogen sulfide (H<sub>2</sub>S), oxygen (O<sub>2</sub>), and lower explosive limit (LEL) concentrations during construction activities at the Site.

## 3. Project Organization

Management of the landfill project is as follows:

### Verogy (Solar Developer)

Brad Parsons, PE, PMP  
Director of Design and Permitting  
(203) 814-6866

### Civil Contractor To be Determined

### Weston & Sampson

Mick Brown  
Health & Safety Manager  
351-322-4799

Robert J. Bukowski, P.E.  
Project Manager  
978-532-1900

This HASP has been prepared to ensure that on Site personnel are advised of known or expected hazards and work activities are performed in accordance with applicable local, state, and Occupational Safety & Health Administration (OSHA) regulations.

All project-related incidents will be reported to the Weston & Sampson Project Manager and Weston & Sampson Health & Safety Manager, within 24 hours of occurrence. A project-related “incident” includes the following types of events:

- Workplace injury (i.e., abrasions, cuts, twisted ankle) or fatality
- Illness (i.e., infection, reaction to a plant exposure or insect bite)
- Major equipment damage or failure
- Property damage (equipment, facility, vehicle, fire, vandalism)
- Unplanned environmental release or exposure (hazardous material)
- Motor Vehicle Accident
- Any work stoppage due to a safety issue (near-miss)

#### **4. Project Staff**

Weston & Sampson personnel are responsible for their personal health and safety and that of their colleagues and must adhere to the procedures established in this HASP. Personnel shall maintain an awareness of Site conditions and exercise sound judgment when confronted with an unsafe and/or (potentially) hazardous condition. If the procedures identified in this HASP do not address an unsafe and/or (potentially) hazardous condition present at the project Site, then Weston & Sampson personnel shall follow a safe course of action and contact the Project Manager or Health & Safety Manager. All Weston & Sampson personnel have the authority to stop work if they become aware of any new unsafe condition or observe unsafe acts by others. These safety-related work stoppages will be immediately reported to the Project Manager and/or Health & Safety Manager. Any unsafe conditions or work practices will be evaluated and corrected prior to re-starting site activities.

#### **5. Hazard Evaluation and Control**

During construction oversight, personnel have the potential to experience warm and cold weather conditions, trip and fall conditions, levels of hydrogen sulfide higher than the Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL) of 20 parts per million (ppm) (Threshold Limit Value (TLV))/1 ppm (Time Weighted Average (TWA)).

Weston & Sampson employees should dress appropriately with personal protective equipment (PPE) including safety glasses, steel-toe boots, and outerwear consistent with the anticipated temperatures (Level D).

#### **6. Site Hazards**

##### **6 a. Chemical Hazards**

Equipment fuel (gasoline or diesel) and hydrogen sulfide are potential chemical hazards that are associated with the Site activities. Further information regarding these chemicals is summarized in the table below.

Table 1. Hazardous Chemicals

Contaminant	Physical Properties	OSHA PEL	Exposure Routes	Signs/ Symptoms of Acute Exposure
Hydrogen Sulfide (H <sub>2</sub> S)	Colorless, odorous gas ("rotten eggs")	20 ppm 1ppm TWA 5 ppm STEL	Inhalation, skin and/or eye contact	Eye, nose and throat irritation, headaches, dizziness, nausea/vomiting, edema, convulsions

It is possible that site personnel will encounter Hydrogen Sulfide (H<sub>2</sub>S) gas during work activities. The OSHA PEL for H<sub>2</sub>S is 20ppm. H<sub>2</sub>S concentrations will be monitored using a 4-gas meter in the worker breathing zone periodically during work activities. All air monitoring results will be recorded on an Air-Monitoring log-sheet (see **Appendix D**). If air monitoring indicates concentrations of H<sub>2</sub>S gas in excess of 1ppm sustained (5 minutes or more), work will be stopped and all personnel will be removed from the work area to a safe location. A plan of action will be developed and implemented to mitigate the elevated H<sub>2</sub>S and work will be resumed following confirmation of safe working conditions (below 10ppm for 15-minutes or more).

See **Section 9** for additional information regarding air monitoring and action levels.

Personnel shall adhere to the following safe work practices when conducting monitoring:

- Smoking, or any other activities that could present an ignition source (i.e., flames, sparks) are strictly prohibited at the Site.
- Avoid confined spaces.

## 6 b. Physical Hazards

Table 2. Physical Hazards

Types of Hazards	Description/Routes of Exposure	Hazard Mitigation Techniques
Slips, Trips & Falls	Falls from height or traditional walking surfaces caused by poor housekeeping, uneven surfaces, walking around equipment, walking in/near excavated areas, etc.	<ul style="list-style-type: none"> <li>• Inspect work areas prior to start of work</li> <li>• Use good housekeeping practices to avoid having extra materials/equipment on-site or blocking traffic</li> <li>• Post warning signs and/or barricades where appropriate</li> <li>• Maintain awareness of site conditions</li> </ul>
Mechanical Equipment (heavy equipment)	Body parts exposed to crushing, caught-between, struck-by, pinch-points or falling objects associated with heavy equipment.	<ul style="list-style-type: none"> <li>• Maintain line of sight with equipment operators</li> <li>• Coordinate equipment movement with foreman</li> <li>• Develop a system of communication between equipment operators and personnel in the vicinity of moving equipment</li> <li>• Establish and delineate the work zone and maintain access to authorized personnel only</li> <li>• Maintain safe distance from moving/operating equipment</li> <li>• Inspect all equipment prior to use, including kill switches</li> <li>• Set up traffic controls/signage (as applicable)</li> <li>• Wear a hard hat and high-visibility vest (or equivalent) when working in the vicinity of moving</li> </ul>

Types of Hazards	Description/Routes of Exposure	Hazard Mitigation Techniques
		equipment
Noise	Noise levels that result in hearing damage or difficulty communicating safety information between on-site personnel.	<ul style="list-style-type: none"> <li>• Review site activities before work begins or in an area where communication is easy</li> <li>• Establish alternate means of communication if verbal commands will be difficult to hear</li> <li>• Use ear plugs or other forms of hearing protection as necessary for sustained noise levels <u>exceeding 85 decibels</u></li> </ul>
Physical/Lifting	Excessive loads or improper lifting techniques resulting in bodily injuries.	<ul style="list-style-type: none"> <li>• Use proper lifting methods, team lifting or assistance devices</li> <li>• Use cut-resistance gloves when handling materials</li> <li>• Wear appropriate safety footwear (steel-toe boots or equivalent) protecting against dropped objects</li> <li>• Use a mechanical device or obtain assistance from other to lift loads greater than 50 pounds</li> </ul>
Vehicular Traffic	Injuries from impacts with vehicular traffic or projectiles caused by passing vehicular traffic and/or heavy equipment	<ul style="list-style-type: none"> <li>• Survey work area, identify traffic patterns, and set up traffic controls in accordance with SOPs and traffic management plan</li> <li>• Establish and delineate the work zone and maintain access to authorized personnel only</li> <li>• All personnel will wear high-visibility clothing (minimum Class 2 vest)</li> <li>• Use of traffic control signs</li> <li>• Coordinate work with police details</li> </ul>
Extreme Temperature	Temperatures that result in heat or cold stress (exhaustion, hypothermia, etc.)	<ul style="list-style-type: none"> <li>• Check weather before going to work</li> <li>• Wear appropriate clothing for predicted weather conditions (i.e., hats, layers for cold, cooling or wicking fabrics for heat)</li> <li>• Maintain adequate hydration</li> <li>• Monitor other staff for signs of heat/cold related illness</li> <li>• Use sun block and other protectants in addition to regular PPE</li> <li>• Maintain open communication with staff</li> </ul>

Types of Hazards	Description/Routes of Exposure	Hazard Mitigation Techniques
Inclement Weather	Weather conditions (rain, snow, ice, etc.) resulting in unsafe site conditions (e.g., slippery surface) and reduced visibility.	<ul style="list-style-type: none"> <li>• Select appropriate clothing based on forecast.</li> <li>• Wear safety footwear with adequate soles for traction</li> <li>• Add traction grips to footwear in icy-snowy conditions</li> <li>• Maintain travel ways and walkways on site for snow, ice, and rain conditions</li> </ul>
Biologic	Insect/animal bites, stings and exposures to allergens, sun exposure	<ul style="list-style-type: none"> <li>• Wash and sanitize hands frequently</li> <li>• Use insect repellants as needed</li> <li>• Use sunscreen and UV protective clothing as needed</li> <li>• Wear appropriate clothing and perform tick checks if working in fields or forested areas</li> </ul>
Dust & Airborne Silica	Inhalation, dermal exposure	<ul style="list-style-type: none"> <li>• Monitor construction activities for sustained visible dust</li> <li>• Use engineering controls, such as wetting, as needed to minimize dust in workers' breathing zone</li> </ul>

## 7. Communication Methods

Site personnel shall have ready access to a mobile telephone or other means of communication (e.g., cellular telephone, two-way radio) for external emergency contact purposes during work activities.

## 8. Personal Protective Equipment

PPE will be used when necessary to reduce exposures to specific worksite hazards. PPE is used when engineering and/or work practice controls cannot eliminate or minimize the hazard to an acceptable safe level. Optional items are identified but may become mandatory PPE as Site hazard conditions change.

Level D protection shall be used during Site activities. This PPE has been selected based on hazards associated with scheduled work activities and anticipated Site conditions. Level D protection includes the mandatory use of the following PPE at all times on site:

- American National Standards Institute (ANSI) approved (Z87.1) safety glasses with side shields
- Safety-toed boots (6" minimum – over the ankle)
- ANSI Class 2 Hi-Vis vests (or equivalent)
- Nitrile gloves, as required for specific tasks where there is a potential for chemical exposure
- Hard hat, as required during heavy equipment use and/or when overhead hazards exist
- Hearing protection, as required for specific tasks where sustained noise levels exceed 85 dB

The following are required equipment for onsite activities but are not PPE or Level D requirements:



- Stocked first aid kit (typical 10-person or equivalent)
- Fire extinguisher (A-B-C rated, 5 lb. minimum)
- Portable eye-wash station (minimum of two 32 oz. bottles)
- Four-gas meter (hydrogen sulfide, oxygen, and LEL)
- Adequate supply of drinking water
- Insect repellent
- Sunscreen
- Cut resistant work gloves (A-2 minimum)
- Portable phone
- Traffic cones
- Caution tape

## 9. Environmental Monitoring

Landfill gas monitoring will be conducted in the operator breathing zone (OBZ) periodically during construction at the Site. Landfill gas tends to collect in low-lying areas under certain atmospheric conditions (e.g., low wind, high humidity, etc.). Landfill gas can migrate upward through the landfill surface into the landfill gas collection system (if present) or other openings, through the surface soils into ambient air. Landfill gas can also migrate horizontally through solid waste, in utility conduits or structures, etc. The following constituents may be associated with landfill gas.

**Hydrogen Sulfide** - is gas that is colorless, odiferous (rotten egg smell), flammable, and heavier than air. Hydrogen sulfide is often produced from decaying waste and organic matter which are common in a capped landfill. Hydrogen sulfide is toxic at relatively low concentrations. The ACGIH TLV is 1 ppm, and the short-term exposure limit (STEL) is 5 ppm; therefore, a conservative action level has been set for the site at <1 ppm.

**Flammable Gases/Vapors** – these will be measured (collectively) as a percentage of the LEL. The site action level is set at 5% LEL.

**Oxygen (O<sub>2</sub>)** - the established safe oxygen range per OSHA is 19.5% - 23.5%. An atmosphere containing oxygen at concentrations <19.5% is considered to be oxygen deficient and a condition that is immediately dangerous to life and health (IDLH). An atmosphere containing oxygen at concentrations >23.5% is considered to be oxygen enriched. Oxygen concentrations below 8% do not support the combustion process.

The established action levels for the parameters described above at the point of operation and OBZ are outlined below:

Table 3. Point of Operation and Operator Breathing Zone

Hydrogen Sulfide	LEL	Oxygen	Action
Monitor OBZ	Monitor Source	Monitor OBZ	
<1ppm	<10%	19.5% - 23.5%	Proceed with work. Use caution by checking the meter frequently.
≥1ppm	≥ 10%	<19.5 % or > 23.5%	<p>Stop current activities and move away from the area to allow time for landfill gas to dissipate.</p> <p>Continue to monitor at the work area and the surrounding area perimeter. Measure LEL and O<sub>2</sub> values again. If after 20 minutes, the action levels continue to be outside of the established limits, evacuate the area and contract the Project Manager and Health &amp; Safety Manager. Tools and equipment/materials that can create a spark or could generate static electricity must stay outside of the work area if LEL readings are detected at 10% or greater.</p> <p>The project team may need to consider the use of engineering controls (e.g., fan, intrinsically safe equipment, non-sparking tools, spark arrestors) if LEL readings at source are 10% or consider return with ventilation system and spark proof/ intrinsically safe equipment.</p>

The presence of nuisance odors, vapors or dust shall immediately warrant the implementation of engineering controls to mitigate emissions. If nuisance odors continue after the implementation of these controls, then activities will be temporarily suspended, and additional measures shall be discussed to remove the source of odor. Personnel will remain upwind of the detected nuisance odors until the situation has dissipated or additional measures have been authorized. The PPE required to provide the appropriate level of dermal and respiratory protection shall be determined based on the results of air monitoring performed and the standards set forth herein.

Table 4. LEL Measurements

LEL Measurement	Condition	Action
10%	Release to the environment that results in the presence of oil and/or hazardous vapors (landfill gases) within buildings, structures, or underground utility conduits (excluding gas control, gas recovery and leachate collection system components) at a concentration of 10% (or greater) of the LEL. This does not include gas control, gas recovery and leachate collection system components.	1. Take immediate action to protect human health and safety;
25%	Concentration of the explosive gases exceed 25% of the LEL for individual components, LEL for individual components or total LEL at the property boundary or beyond (not including off-site buildings, structures or utility conduits covered under 10% of the LEL condition above).	1. Take immediate action to protect human health and safety;

## 10. Training and Medical Surveillance

### a. Training

Personnel conducting site work shall have completed the Initial Training as required by the OSHA in 29 CFR 1910.120 Hazardous Waste Operations and Emergency Response (HAZWOPER) course and a minimum of three days of supervised actual field experience. Site employees shall also receive annual 8-hour HAZWOPER refresher training.

Site employees will be provided with a copy of this HASP. Site employees are expected to thoroughly read and understand information contained in the HASP prior to conducting site activities. Staff will acknowledge their receipt and understanding of this HASP by signature in the form provided as **Appendix B**.

### b. Medical Surveillance

All personnel involved in the project may be required to participate in the Weston & Sampson's medical surveillance program. This program follows the provisions set forth by OSHA in 29 CFR 1910.120, and includes the performance of annual occupational medical examinations under a licensed occupational physician.

## 11. Site Control Measures

### a. General Control Measures

The following general Site control measures shall be implemented by Weston & Sampson employees working on this project:

- The work area shall be carefully assessed for safety hazards prior to conducting work.
- Visibly contaminated areas should be avoided when possible.

- No eating, drinking, or smoking is allowed in contaminated areas or decontamination zones.

b. Safety Briefings

The On-Site Coordinator shall conduct a Site safety briefing (Daily Tailgate Meetings) before starting field activities or as tasks and/or site conditions change.

Site safety briefings will consist of a general discussion of the HASP, Site-specific hazards, hazards associated with specific tasks and/or equipment, location of work zones, PPE requirements, equipment, special procedures, emergency procedures, and any other pertinent health and safety information. All daily safety briefings, including topics discussed and attendees, will be documented using the “Daily Tailgate Meeting” form provided as **Appendix C**.

c. Worksite Set Up

When setting up the worksite, Weston & Sampson employees shall review these procedures. However, based on location and traffic, a work set-up zone as described may not be necessary. Therefore, portions of the section will be used as appropriate:

- Secure area from unauthorized entry by erecting traffic cones, pylons, or other diversion devices around the work zone. Caution tape can also be used with cones/pylons to further delineate work zones.
- Establish decontamination procedures as needed
- Utilize access control at the entry and exit from the work zone.
- Establish onsite communications, as appropriate. These consist of line-of-sight, hand signals, and verbal communication.
- Establish emergency signals, as appropriate.
- Establish a “buddy system.”
- Establish procedures for disposal of waste materials generated onsite.

The On-Site Coordinator will conduct periodic assessments of work practices to evaluate the effectiveness of this HASP, as necessary. Deficiencies in personnel adherence to work practices identified in this HASP will immediately be corrected. Deficiencies in the HASP itself will be corrected by the Health & Safety Manager prior to implementation.

Personnel shall wash hands and other affected body parts with soap and water prior to breaks, when leaving the Site, and when potentially contaminated equipment/material comes in direct contact with the skin.

Wastes (e.g., PPE – gloves, safety glasses, etc.) generated from decontamination activities shall be bagged and properly disposed.

## 12. Emergency Response

a. Pre-Planning Activities

The On-Site Coordinator shall perform the following pre-planning activities prior to the initiation of field activities:

- Locate nearest telephone to the work site and assess on-site communications.
- Identify chemical and safety hazards.
- Confirm emergency telephone numbers and route(s) to hospital (see **Appendix A**).
- Review project plan for anticipated Site conditions, any alterations in on-site operations, and personnel availability.
- Ensure the project team has travel first aid kits, portable eyewash, and working fire extinguisher.
- Check Site emergency equipment operational status and supply inventory.
- Locate emergency information (e.g., evacuation routes) and designated assembly point on site map.
- Assemble emergency contact, hospital route, evacuation route, and assembly point information.

Emergency pre-planning information is detailed in **Appendix A** of this HASP.

b. Evacuation Procedures

In the event of an emergency at the worksite, Weston & Sampson personnel will immediately evacuate the work area and proceed to the designated muster point (see Figure 1.). Site personnel shall then begin notifying appropriate emergency and Weston & Sampson contacts as identified in **Appendix A**.




Figure 1. Emergency Evacuation Muster Locations

c. Medical Emergencies

The local medical emergency facility for the project is:

**Backus Hospital**  
326 Washington St.  
Norwich, CT 06360  
(860) 889-8331

A map and directions to Backus Hospital is provided in **Appendix A**.

The following procedures shall be implemented by Weston & Sampson employees in the event of a medical emergency:

- Stop field work activities.
- Summon assistance (on and offsite), as necessary.
- Prevent further injury and maintain personal safety.
- Maintain scene safety and prevent access by unauthorized personnel.
- If the scene is safe, and if trained in and comfortable with performing first aid tasks, initiate first aid, as appropriate.
- Supply medical providers with information about the accident/incident.
- Notify the Project Manager, the Health & Safety Manager and the HR Manager of the accident/incident.

d. Accident/Incident Reports

The On-Site Coordinator shall complete an Incident Report Form (obtained from the Health & Safety Manager) as soon as possible, but no later than 24 hours, after any accident/incident occurrence. Copies of these forms shall be sent to the Project Manager, Health & Safety Manager, and the Human Resources Manager.

### **13. Plan Approval**

This HASP for the Montville Landfill Solar Construction has been written for use by Weston & Sampson employees. Weston & Sampson claims no responsibility for its use by others, unless specified and defined in project or contract documents. This HASP is written for the specific Site conditions, purposes, dates, and personnel specified and must be amended if these conditions change.

## APPENDIX A

### EMERGENCY CONTACT INFORMATION AND PROCEDURES


Nearest Telephone:	Cell phone
Chemical and Safety Hazards Not Covered in General HASP:	None
Utility Clearance Permit Number:	
Emergency Telephone Numbers:	
Local Police:	911
Fire Department:	911
Ambulance:	911
State Police:	(860) 685-8190
Hospital/Emergency Care:	Backus Hospital 326 Washington St. Norwich, CT 06360 (860) 889-8331
Weston & Sampson: Health & Safety Manager	Mick Brown (351) 322-4799
Project Manager:	Robert Bukowski (978) 532-1900



### **HOSPITAL DIRECTIONS Backus Hospital - Norwich**

- Starting route at 669 Oakdale Rd. Montville, CT 06370 Travel to I-395N from Oakdale Rd and CT-163 toward Chesterfield Rd (3.1 mi)
- Continue on I-395 (7 mi)
- Take exit 13A to merge onto CT-2 E/CT-32 S toward Norwich (1.2 mi)
- Take the CT-2 E/CT-32 S exit toward Downtown (341 ft)
- Turn right onto CT-2 E/CT-32 S/Washington St. (289 ft)
- Turn right onto Backus St, destination will be on right (203 ft)
- Arrive at Backus Hospital, 326 Washington St, Norwich, CT 06360

BACKUS HOSPITAL MAP  
326 Washington St.  
Norwich, CT



## APPENDIX B

### EMPLOYEE HASP REVIEW SIGNATURE SHEET

“By signing this form, I verify that I have been provided with a copy of this HASP and have read it. I understand and agree to abide by the provisions of this HASP.”

EMPLOYEE NAME (print)	EMPLOYEE SIGNATURE	DATE

## APPENDIX C

### DAILY TAILGATE MEETING ATTENDANCE RECORD

Daily Tailgate Meetings should be conducted by the Weston & Sampson project/site safety manager and/or field supervisor. All tasks planned, associated hazards, and actions to mitigate those hazards should be reviewed. All personnel in attendance are to sign below.

Meeting Held By: \_\_\_\_\_

Topics Reviewed:

---

---

---

"By signing this form, I verify that I have attended a Site health and safety tailgate meeting prior to commencement of field activities"

PRINT NAME AND COMPANY	SIGNATURE	DATE

APPENDIX D  
AIR MONITORING LOG SHEET

