

FULLER ENGINEERING & LAND SURVEYING, LLC

525 John Street • Second Floor

Bridgeport, CT 06604

(203) 333-9465 (203) 336-1769 FAX


ENGINEERING REPORT

Project Name:

**Madison Place
Luxury Townhouse Development
18 Powerhouse Road &
145 CT Route 32
Montville, CT**

Information prepared for:

**JNE Holdings, LLC
&
Town of Montville
Department of Public Works / Engineering Department**



Dated: January 11 February 2025

Revised 18 April 2025

**FULLER ENGINEERING & LAND SURVEYING, LLC
525 JOHN STREET 2ND FLOOR BRIDGEPORT, CONNECTICUT 06604
PHONE (203)333-9465; FAX (203)336-1769**

TABLE OF CONTENTS (Stormwater Study)

| | |
|--|----------------|
| Introduction | 1 |
| Narrative | 1 |
| Modifications to this Report | 1 |
| Pre-Development Conditions | 2 |
| Proposed Post Development Conditions | 2 |
| Calculations | 2 |
| Basin 'A' | 2 |
| Basin 'B' | 3 |
| Summary Basin 'A' | 4 |
| Summary Basin 'B' | 4 |
| Conclusion | 4 |
| Soil Erosion and Sedimentation Control (All Phases) | 5 |
| Montville Precipitation Frequency (PF) Rainfall Data | Appendix A |
| NRCS Soil Map & Hydrologic Soil Group Rating | Appendix B |
| HydroCAD Analysis – Basin A Powerhouse Road | Appendix C |
| HydroCAD Analysis – Basin B Route 32 | Appendix D |
| Drainage Area Maps | Appendix E |
| Pipe Flow Calculations | Appendix F |
| Operations and Maintenance Plan | Appendix G |

FULLER ENGINEERING & LAND SURVEYING, LLC

525 John Street – Second Floor – Bridgeport, CT 06604

Phone: (203) 333-9465

Fax: (203) 336-1769

STORMWATER STUDY

APPLICANT: JNE HOLDINGS, LLC

PROJECT LOCATION: WILTONS WAY 18 Powerhouse Road & 145 Route 32,
Montville, Connecticut

INTRODUCTION

The proposed project consists of the merger of two parcels into one lot consisting of 110,146 S.F.:

145 CT Route 23

Site Area: 59,415 S.F.

One existing 4 family residential unit.

18 Powerhouse Road

Site Area 50,731 S.F.

One existing 2 family residential unit.

The proposed project is anticipated to be constructed in three phases.

DRAINAGE STUDY

NARRATIVE

The subject of this report is a 1.185 acre portion of a parcel located at 145 Route 32 in Monteville.. The purpose of this report is to determine the existing and proposed runoffs resulting from the proposed site improvements in order to design a stormwater management system.

MODIFICATIONS TO THIS REPORT

The previous drainage report revised through March 7, 2025 analyzed the drainage areas into two separate phases. Based on comments from the Town Engineer, this report has been restructured into two overall drainage basins:

1. Basin 'A' - The largest watershed area which flows to the east and consists primarily of the proposed development
2. Basin 'B' - The smaller watershed area flowing toward CT Route 32.

The individual phase calculations have been eliminated from this report and replaced by analysis of Basins 'A', and 'B' individual watersheds. Basin 'A' now merges and analyzes Phase 1 and Phase 2 together through the 'Combined' portion of the analysis.

FULLER ENGINEERING & LAND SURVEYING, LLC
525 JOHN STREET 2ND FLOOR BRIDGEPORT, CONNECTICUT 06604
PHONE (203)333-9465; FAX (203)336-1769

PRE-DEVELOPMENT CONDITIONS

The subject parcel is located on the west side of Route 32, at its intersection with Powerhouse Road. The lot currently contains buildings and a driveway. There are two watershed basins on the property, one draining to the west and Route 32 and the other to the east.

Existing soils at this location, as identified in the NRCS Soil Survey of Fairfield County, Connecticut, consist of Narragansett silt loam, 2 to 8 percent slopes, which has a Hydrologic classification of "B".

The existing runoff from a 100-Year rainfall event in Basin A is 8.00 c.f.s.
The existing runoff from a 100-Year rainfall event in Basin B is 3.06 c.f.s.

PROPOSED POST-DEVELOPMENT CONDITIONS

The proposal for this phase is to construct a total of 11 residential units, with associated driveway.

The area of Basin A increases by the same amount as Basin B decreases due to the proposed construction.

The proposed runoff (prior to mitigation) from a 100-Year rainfall event in Basin A is 12.44 c.f.s.
The proposed runoff (prior to mitigation) from a 100-Year rainfall event in Basin B is 2.95 c.f.s.

CALCULATIONS

The following computations of the existing and proposed conditions runoff flows were derived from the HydroCAD computer software. HydroCAD follows the NRCS TR-20 procedure for computing stormwater runoff. Computations were performed for a 50-year storm event, which has a 2% chance of occurring in any given 12 month period.

BASIN 'A'

Existing Conditions (Basin A):

| | | |
|------------------|--------------------|-------|
| House | 1,382 s.f. | CN 98 |
| Driveway | 1,696 s.f. | CN 98 |
| Garage | 764 s.f. | CN 98 |
| Concrete Slab | 246 s.f. | CN 98 |
| Shed | 373 s.f. | CN 98 |
| Walks | 221 s.f. | CN 98 |
| House Basin B | 200 s.f. | CN 98 |
| Driveway Basin B | 1,169 s.f. | CN 98 |
| Lawn | 82,223 s.f. | CN 69 |
| Total | 88,274 s.f. | |

Weighted CN - **71**

Proposed Conditions (Basin A):

| | | |
|------------------|-------------|-------|
| Buildings | 14,182 s.f. | CN 98 |
| Driveway/Parking | 16,150 s.f. | CN 98 |
| Lawn | 58,665 s.f. | CN 69 |
| Total | 88,997 s.f. | |

Weighted CN - **79**

Groundwater Recharge Volume (GWV) Basin A:

Impervious area = 34.1 %

WQV = $(0.3569 * 2.043 \text{ ac}) / 12 \times 1.3 = 0.0789908 \text{ ac-ft} = 3,440.8 \text{ ft}^3$

GWV = $3,440.8 * 0.25 = 860.2 \text{ ft}^3$

BASIN 'B'

Existing Conditions (Basin B):

| | | |
|----------|-------------|-------|
| House | 1,659 s.f. | CN 98 |
| Driveway | 1,934 s.f. | CN 98 |
| Gravel | 836 s.f. | CN 85 |
| Walks | 196 s.f. | CN 98 |
| Lawn | 16,768 s.f. | CN 69 |
| Total | 21,393 s.f. | |

Weighted CN - **75**

Proposed Conditions (Basin B):

| | | |
|----------|-------------|-------|
| House | 1,659 s.f. | CN 98 |
| Building | 1,046 s.f. | CN 98 |
| Driveway | 1,271 s.f. | CN 98 |
| Lawn | 16,694 s.f. | CN 69 |
| Total - | 20,670 s.f. | |

Weighted CN - **75**

SUMMARY Basin A:

| | 100 Year | 50 Year | 25Yr. | 10Yr. | 5Yr. | 2Yr. |
|---|-------------|-------------|-------|-------|------|------|
| Existing Runoff : | 8.00 | 6.73 c.f.s | 5.48 | 3.93 | 2.86 | 1.68 |
| Proposed Runoff : | 12.44 | 10.72 c.f.s | 9.04 | 6.85 | 5.30 | 3.49 |
| Runoff Retained: | 4.78 | 4.26 c.f.s | 3.75 | 3.08 | 2.60 | 2.01 |
| Areas Bypassing Retention Plus overflow: | 7.60 | 6.41 c.f.s | 5.24 | 3.78 | 2.76 | 1.64 |

SUMMARY Basin B:

| | 100 Year | 50 Year | 25Yr. | 10Yr. | 5Yr. | 2Yr. |
|-------------------|-------------|-------------|-------|-------|------|------|
| Existing Runoff : | 3.06 | 2.61 c.f.s | 2.17 | 1.61 | 1.21 | 0.76 |
| Proposed Runoff : | 2.95 | 2.52 c.f.s. | 2.10 | 1.55 | 1.17 | 0.74 |

CONCLUSION:

The increased runoff resulting from the proposed site improvements will be retained in an on-site retention system. The runoff from the driveway and the roof of the northern building in Basin A will be routed to a total of 352 linear feet of 48" concrete galleries. The galleries consisting of two sets, the 160 linear feet to mitigate the Phase 1 of construction and the set of 192 linear feet for the remainder in Basin A. The increase in stormwater runoff is mitigated on-site.

This system will reduce the net peak run-off during a 100 Year (2%) rainfall event in Basin A to 7.60 c.f.s. from its current peak of 8.00 c.f.s.

The bottom of the eastern set of concrete galleries will be at elevation 98.6. No restrictive layer was found to an elevation of 97.0. The bottom of the western set of concrete galleries will be at elevation 93.9. No restrictive layer was found to an elevation of 92.0.

The proposed retention system in Basin A provides a total of 5,750 ft³ of storage, which will be adequate to maintain the net runoff during a 100 Year rainfall event, meets the Water Quality Volume and will provide groundwater recharge.

The maximum peak net runoff from the proposed conditions decrease compared to the peak runoff from the existing conditions for each of the rainfall events in Basin A from the 2 Year to the 100 Year rainfall events, as the table above illustrates.

The runoff in Basin B conditions decrease compared to the peak runoff from the existing conditions for each of the rainfall events from the 2 Year to the 100 Year rainfall events, as the table above illustrates, due to a reduction of 74 square feet of impervious surfaces.

The proposed improvements will have no adverse impact on surrounding properties.

SOIL EROSION AND SEDIMENTATION CONTROL (All Phases)

For temporary condition or during construction a silt fence shall be provided along the property lines. Anti-tracking aprons shall be provided at all access routes from the site to the public road. A temporary diversion berm with stone check dams @ 50 ft o.c. shall be maintained and relocated as required during construction. All planting areas shall be protected with slope stabilization measures.


For permanent condition, all embankments, after being stabilized, shall be seeded to lawn or seed mixture as specified. Newly planted areas shall be covered with straw or erosion control blankets.

APPENDIX “A”

MONTVILLE PRECIPITATION FREQUENCY (PF)
RAINFALL DATA

NOAA ATLAS 14 POINT PRECIPITATION FREQUENCY ESTIMATES: CT

#245 Norwich New London Road (CT State RTE. 32) Montville, CT





NOAA Atlas 14, Volume 10, Version 3
Location name: Uncasville, Connecticut, USA*
Latitude: 41.4331°, Longitude: -72.1092°
Elevation: 67.49 ft**
* source: ESRI Maps
** source: USGS



POINT PRECIPITATION FREQUENCY ESTIMATES

Sanja Perica, Sandra Pavlovic, Michael St. Laurent, Carl Trypaluk, Dale Unruh, Orlan Wilhite

NOAA, National Weather Service, Silver Spring, Maryland

[PF_tabular](#) | [PF_graphical](#) | [Maps & aerals](#)



PF tabular

| PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches) ¹ | | | | | | | | | | |
|---|-------------------------------------|------------------------|------------------------|------------------------|------------------------|-----------------------|-----------------------|----------------------|----------------------|----------------------|
| Duration | Average recurrence interval (years) | | | | | | | | | |
| | 1 | 2 | 5 | 10 | 25 | 50 | 100 | 200 | 500 | 1000 |
| 5-min | 0.340 (0.266-0.427) | 0.406 (0.317-0.510) | 0.514 (0.400-0.648) | 0.604 (0.467-0.763) | 0.727 (0.545-0.952) | 0.820 (0.601-1.09) | 0.918 (0.654-1.26) | 1.03 (0.693-1.43) | 1.19 (0.770-1.70) | 1.32 (0.835-1.91) |
| 10-min | 0.482 (0.377-0.605) | 0.576 (0.449-0.723) | 0.729 (0.567-0.918) | 0.856 (0.662-1.08) | 1.03 (0.772-1.35) | 1.16 (0.853-1.55) | 1.30 (0.926-1.78) | 1.46 (0.982-2.02) | 1.68 (1.09-2.40) | 1.87 (1.18-2.71) |
| 15-min | 0.567 (0.443-0.712) | 0.677 (0.529-0.851) | 0.857 (0.667-1.08) | 1.01 (0.779-1.27) | 1.21 (0.908-1.59) | 1.37 (1.00-1.82) | 1.53 (1.09-2.10) | 1.71 (1.16-2.38) | 1.98 (1.28-2.83) | 2.20 (1.39-3.19) |
| 30-min | 0.803 (0.627-1.01) | 0.958 (0.747-1.20) | 1.21 (0.942-1.53) | 1.42 (1.10-1.80) | 1.71 (1.28-2.24) | 1.93 (1.41-2.57) | 2.16 (1.54-2.96) | 2.42 (1.63-3.36) | 2.79 (1.81-3.99) | 3.10 (1.96-4.50) |
| 60-min | 1.04 (0.811-1.30) | 1.24 (0.966-1.56) | 1.57 (1.22-1.97) | 1.84 (1.42-2.32) | 2.21 (1.66-2.89) | 2.49 (1.83-3.32) | 2.79 (1.99-3.82) | 3.12 (2.10-4.34) | 3.61 (2.34-5.15) | 4.01 (2.53-5.81) |
| 2-hr | 1.36 (1.08-1.70) | 1.63 (1.28-2.03) | 2.05 (1.61-2.57) | 2.41 (1.88-3.02) | 2.90 (2.19-3.77) | 3.26 (2.41-4.31) | 3.65 (2.62-4.97) | 4.10 (2.78-5.65) | 4.75 (3.09-6.72) | 5.28 (3.36-7.59) |
| 3-hr | 1.58 (1.25-1.96) | 1.89 (1.49-2.34) | 2.38 (1.88-2.96) | 2.79 (2.19-3.48) | 3.35 (2.54-4.34) | 3.78 (2.81-4.97) | 4.22 (3.05-5.73) | 4.74 (3.22-6.50) | 5.49 (3.59-7.74) | 6.12 (3.90-8.75) |
| 6-hr | 2.01 (1.60-2.47) | 2.39 (1.90-2.94) | 3.00 (2.39-3.70) | 3.51 (2.78-4.35) | 4.22 (3.22-5.41) | 4.75 (3.55-6.19) | 5.30 (3.85-7.13) | 5.95 (4.07-8.08) | 6.89 (4.52-9.61) | 7.67 (4.91-10.9) |
| 12-hr | 2.48 (2.00-3.02) | 2.94 (2.36-3.59) | 3.69 (2.96-4.52) | 4.31 (3.44-5.30) | 5.17 (3.98-6.58) | 5.81 (4.38-7.52) | 6.49 (4.74-8.65) | 7.28 (5.00-9.80) | 8.42 (5.55-11.6) | 9.37 (6.02-13.2) |
| 24-hr | 2.90 (2.36-3.51) | 3.46 (2.80-4.18) | 4.36 (3.53-5.30) | 5.12 (4.11-6.24) | 6.15 (4.77-7.77) | 6.93 (5.26-8.89) | 7.75 (5.71-10.3) | 8.71 (6.02-11.6) | 10.1 (6.71-13.9) | 11.3 (7.31-15.7) |
| 2-day | 3.25 (2.66-3.89) | 3.91 (3.20-4.69) | 4.99 (4.06-6.00) | 5.88 (4.77-7.11) | 7.12 (5.57-8.92) | 8.03 (6.15-10.3) | 9.02 (6.71-11.9) | 10.2 (7.09-13.5) | 12.0 (7.97-16.3) | 13.5 (8.75-18.6) |
| 3-day | 3.52 (2.90-4.20) | 4.23 (3.48-5.06) | 5.40 (4.43-6.47) | 6.37 (5.19-7.66) | 7.70 (6.06-9.62) | 8.69 (6.69-11.0) | 9.76 (7.29-12.8) | 11.0 (7.70-14.5) | 13.0 (8.66-17.5) | 14.6 (9.51-20.0) |
| 4-day | 3.78 (3.12-4.50) | 4.53 (3.74-5.39) | 5.75 (4.73-6.87) | 6.77 (5.53-8.12) | 8.17 (6.45-10.2) | 9.21 (7.11-11.7) | 10.3 (7.73-13.5) | 11.7 (8.15-15.3) | 13.7 (9.16-18.4) | 15.4 (10.0-21.0) |
| 7-day | 4.50 (3.75-5.33) | 5.32 (4.43-6.30) | 6.66 (5.52-7.90) | 7.77 (6.40-9.26) | 9.30 (7.38-11.5) | 10.4 (8.10-13.1) | 11.7 (8.75-15.1) | 13.1 (9.20-17.0) | 15.2 (10.2-20.3) | 17.0 (11.1-23.1) |
| 10-day | 5.22 (4.37-6.15) | 6.08 (5.08-7.16) | 7.48 (6.22-8.83) | 8.64 (7.14-10.2) | 10.2 (8.16-12.5) | 11.4 (8.90-14.2) | 12.7 (9.55-16.3) | 14.2 (9.99-18.4) | 16.3 (11.0-21.6) | 18.0 (11.8-24.3) |
| 20-day | 7.42 (6.26-8.66) | 8.33 (7.03-9.74) | 9.83 (8.25-11.5) | 11.1 (9.23-13.0) | 12.8 (10.2-15.4) | 14.1 (11.0-17.2) | 15.4 (11.5-19.3) | 16.8 (11.9-21.5) | 18.7 (12.7-24.6) | 20.1 (13.3-26.9) |
| 30-day | 9.25 (7.85-10.7) | 10.2 (8.65-11.9) | 11.8 (9.92-13.7) | 13.0 (10.9-15.3) | 14.8 (11.9-17.7) | 16.2 (12.7-19.6) | 17.5 (13.1-21.7) | 18.9 (13.5-24.0) | 20.5 (14.0-26.8) | 21.7 (14.4-28.9) |
| 45-day | 11.5 (9.82-13.3) | 12.5 (10.7-14.5) | 14.1 (12.0-16.4) | 15.5 (13.1-18.0) | 17.4 (14.0-20.7) | 18.9 (14.8-22.7) | 20.3 (15.2-24.8) | 21.5 (15.4-27.2) | 23.0 (15.7-29.9) | 24.0 (15.9-31.7) |
| 60-day | 13.4 (11.5-15.4) | 14.4 (12.3-16.6) | 16.2 (13.8-18.7) | 17.6 (14.9-20.4) | 19.6 (15.8-23.1) | 21.1 (16.6-25.3) | 22.6 (16.9-27.5) | 23.8 (17.1-30.0) | 25.2 (17.3-32.6) | 26.1 (17.4-34.3) |
| ¹ Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS). Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values. Please refer to NOAA Atlas 14 document for more information. | | | | | | | | | | |

[Back to Top](#)


PF graphical

PDS-based depth-duration-frequency (DDF) curves
Latitude: 41.4331°, Longitude: -72.1092°




Maps & aerials

Small scale terrain



Large scale terrain



Large scale map



Large scale aerial



[Back to Top](#)

[US Department of Commerce](#)
[National Oceanic and Atmospheric Administration](#)
[National Weather Service](#)
[National Water Center](#)
1325 East West Highway
Silver Spring, MD 20910
Questions?: HDSC.Questions@noaa.gov

[Disclaimer](#)


APPENDIX “B”

NRCS SOIL MAP AND HYDROLOGIC SOIL GROUP RATINGS

Soil Map—State of Connecticut, Eastern Part



Soil Map may not be valid at this scale.




**Natural Resources
Conservation Service**

Web Soil Survey
National Cooperative Soil Survey


2/8/2025
Page 1 of 3


MAP LEGEND

Area of Interest (AOI)

 Area of Interest (AOI)

Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

Special Point Features



Blowout



Borrow Pit



Clay Spot



Closed Depression



Gravel Pit



Gravelly Spot



Landfill



Lava Flow



Marsh or swamp



Mine or Quarry



Miscellaneous Water



Perennial Water



Rock Outcrop



Saline Spot



Sandy Spot



Severely Eroded Spot



Sinkhole



Slide or Slip



Sodic Spot



Spoil Area



Stony Spot



Very Stony Spot



Wet Spot



Other



Special Line Features

Water Features



Streams and Canals

Transportation



Rails



Interstate Highways



US Routes



Major Roads



Local Roads

Background



Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:12,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: State of Connecticut, Eastern Part

Survey Area Data: Version 2, Aug 30, 2024

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 14, 2022—Oct 6, 2022


The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend



| Map Unit Symbol | Map Unit Name | Acres in AOI | Percent of AOI |
|------------------------------------|---|--------------|----------------|
| 38C | Hinckley loamy sand, 3 to 15 percent slopes | 0.1 | 3.2% |
| 66B | Narragansett silt loam, 2 to 8 percent slopes | 2.4 | 96.0% |
| 68C | Narragansett silt loam, 3 to 15 percent slopes, extremely stony | 0.0 | 0.7% |
| Totals for Area of Interest | | 2.5 | 100.0% |

APPENDIX “C”

**HydroCAD Analysis
Basin A
Powerhouse Road**



Existing Conditions Basin A Powerhouse Road



Routing Diagram for 2578ExistingRev1

Prepared by Fairfield County Engineering LLC, Printed 4/17/2025
HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC


Summary for Subcatchment 1S: Existing Conditions Basin A Powerhouse Road

Runoff = 1.68 cfs @ 12.27 hrs, Volume= 0.183 af, Depth> 1.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,382 | 98 | House |
| * | 1,696 | 98 | Driveway |
| * | 764 | 98 | Garage |
| * | 246 | 98 | Concrete Slab |
| * | 373 | 98 | Shed |
| * | 221 | 98 | Walks |
| * | 200 | 98 | House Basin B |
| * | 1,169 | 98 | Driveway Basin B |
| | 82,223 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,274 | 71 | Weighted Average |
| | 82,223 | | 93.15% Pervious Area |
| | 6,051 | | 6.85% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|---|
| 15.8 | 162 | 0.0140 | 0.17 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.3 | 199 | 0.1390 | 2.61 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 17.1 | 361 | Total | | | |

Subcatchment 1S: Existing Conditions Basin A Powerhouse Road


Summary for Subcatchment 1S: Existing Conditions Basin A Powerhouse Road

Runoff = 2.86 cfs @ 12.27 hrs, Volume= 0.300 af, Depth> 1.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,382 | 98 | House |
| * 1,696 | 98 | Driveway |
| * 764 | 98 | Garage |
| * 246 | 98 | Concrete Slab |
| * 373 | 98 | Shed |
| * 221 | 98 | Walks |
| * 200 | 98 | House Basin B |
| * 1,169 | 98 | Driveway Basin B |
| 82,223 | 69 | 50-75% Grass cover, Fair, HSG B |
| 88,274 | 71 | Weighted Average |
| 82,223 | | 93.15% Pervious Area |
| 6,051 | | 6.85% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 15.8 | 162 | 0.0140 | 0.17 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.3 | 199 | 0.1390 | 2.61 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 17.1 | 361 | Total | | | |

Subcatchment 1S: Existing Conditions Basin A Powerhouse Road


Summary for Subcatchment 1S: Existing Conditions Basin A Powerhouse Road

Runoff = 3.93 cfs @ 12.26 hrs, Volume= 0.406 af, Depth> 2.40"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,382 | 98 | House |
| * 1,696 | 98 | Driveway |
| * 764 | 98 | Garage |
| * 246 | 98 | Concrete Slab |
| * 373 | 98 | Shed |
| * 221 | 98 | Walks |
| * 200 | 98 | House Basin B |
| * 1,169 | 98 | Driveway Basin B |
| 82,223 | 69 | 50-75% Grass cover, Fair, HSG B |
| 88,274 | 71 | Weighted Average |
| 82,223 | | 93.15% Pervious Area |
| 6,051 | | 6.85% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 15.8 | 162 | 0.0140 | 0.17 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.3 | 199 | 0.1390 | 2.61 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 17.1 | 361 | Total | | | |

Subcatchment 1S: Existing Conditions Basin A Powerhouse Road


Summary for Subcatchment 1S: Existing Conditions Basin A Powerhouse Road

Runoff = 5.48 cfs @ 12.26 hrs, Volume= 0.563 af, Depth> 3.33"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,382 | 98 | House |
| * 1,696 | 98 | Driveway |
| * 764 | 98 | Garage |
| * 246 | 98 | Concrete Slab |
| * 373 | 98 | Shed |
| * 221 | 98 | Walks |
| * 200 | 98 | House Basin B |
| * 1,169 | 98 | Driveway Basin B |
| 82,223 | 69 | 50-75% Grass cover, Fair, HSG B |
| 88,274 | 71 | Weighted Average |
| 82,223 | | 93.15% Pervious Area |
| 6,051 | | 6.85% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 15.8 | 162 | 0.0140 | 0.17 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.3 | 199 | 0.1390 | 2.61 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 17.1 | 361 | Total | | | |

Subcatchment 1S: Existing Conditions Basin A Powerhouse Road


Summary for Subcatchment 1S: Existing Conditions Basin A Powerhouse Road

Runoff = 6.73 cfs @ 12.26 hrs, Volume= 0.689 af, Depth> 4.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,382 | 98 | House |
| * 1,696 | 98 | Driveway |
| * 764 | 98 | Garage |
| * 246 | 98 | Concrete Slab |
| * 373 | 98 | Shed |
| * 221 | 98 | Walks |
| * 200 | 98 | House Basin B |
| * 1,169 | 98 | Driveway Basin B |
| 82,223 | 69 | 50-75% Grass cover, Fair, HSG B |
| 88,274 | 71 | Weighted Average |
| 82,223 | | 93.15% Pervious Area |
| 6,051 | | 6.85% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 15.8 | 162 | 0.0140 | 0.17 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.3 | 199 | 0.1390 | 2.61 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 17.1 | 361 | Total | | | |

Subcatchment 1S: Existing Conditions Basin A Powerhouse Road


Summary for Subcatchment 1S: Existing Conditions Basin A Powerhouse Road


Runoff = 8.00 cfs @ 12.26 hrs, Volume= 0.820 af, Depth> 4.86"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"



| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,382 | 98 | House |
| * 1,696 | 98 | Driveway |
| * 764 | 98 | Garage |
| * 246 | 98 | Concrete Slab |
| * 373 | 98 | Shed |
| * 221 | 98 | Walks |
| * 200 | 98 | House Basin B |
| * 1,169 | 98 | Driveway Basin B |
| 82,223 | 69 | 50-75% Grass cover, Fair, HSG B |
| 88,274 | 71 | Weighted Average |
| 82,223 | | 93.15% Pervious Area |
| 6,051 | | 6.85% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 15.8 | 162 | 0.0140 | 0.17 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.3 | 199 | 0.1390 | 2.61 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 17.1 | 361 | Total | | | |

Subcatchment 1S: Existing Conditions Basin A Powerhouse Road



Proposed Conditions Basin A Powehouse Road



Routing Diagram for 2578ProposedRev1

Prepared by Fairfield County Engineering LLC, Printed 4/17/2025
HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC


Summary for Subcatchment 2S: Proposed Conditions Basin A Powehouse Road

Runoff = 3.49 cfs @ 12.16 hrs, Volume= 0.271 af, Depth> 1.59"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 14,182 | 98 | Buildings |
| * | 16,150 | 98 | Driveway |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,997 | 79 | Weighted Average |
| | 58,665 | | 65.92% Pervious Area |
| | 30,332 | | 34.08% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin A Powehouse Road


Summary for Subcatchment 2S: Proposed Conditions Basin A Powehouse Road

Runoff = 5.30 cfs @ 12.16 hrs, Volume= 0.411 af, Depth> 2.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 14,182 | 98 | Buildings |
| * | 16,150 | 98 | Driveway |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,997 | 79 | Weighted Average |
| | 58,665 | | 65.92% Pervious Area |
| | 30,332 | | 34.08% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin A Powehouse Road


Summary for Subcatchment 2S: Proposed Conditions Basin A Powehouse Road

Runoff = 6.85 cfs @ 12.15 hrs, Volume= 0.534 af, Depth> 3.13"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 14,182 | 98 | Buildings |
| * | 16,150 | 98 | Driveway |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,997 | 79 | Weighted Average |
| | 58,665 | | 65.92% Pervious Area |
| | 30,332 | | 34.08% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin A Powehouse Road


Summary for Subcatchment 2S: Proposed Conditions Basin A Powehouse Road

Runoff = 9.04 cfs @ 12.15 hrs, Volume= 0.710 af, Depth> 4.17"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 14,182 | 98 | Buildings |
| * | 16,150 | 98 | Driveway |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,997 | 79 | Weighted Average |
| | 58,665 | | 65.92% Pervious Area |
| | 30,332 | | 34.08% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin A Powehouse Road


Summary for Subcatchment 2S: Proposed Conditions Basin A Powehouse Road

Runoff = 10.72 cfs @ 12.15 hrs, Volume= 0.848 af, Depth> 4.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 14,182 | 98 | Buildings |
| * | 16,150 | 98 | Driveway |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,997 | 79 | Weighted Average |
| | 58,665 | | 65.92% Pervious Area |
| | 30,332 | | 34.08% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin A Powehouse Road


Summary for Subcatchment 2S: Proposed Conditions Basin A Powehouse Road


Runoff = 12.44 cfs @ 12.15 hrs, Volume= 0.990 af, Depth> 5.82"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 14,182 | 98 | Buildings |
| * | 16,150 | 98 | Driveway |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 88,997 | 79 | Weighted Average |
| | 58,665 | | 65.92% Pervious Area |
| | 30,332 | | 34.08% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin A Powehouse Road




Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 0.72 cfs @ 12.11 hrs, Volume= 0.057 af, Depth> 3.30"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| Area (sf) | CN | Description |
|-----------|----|-------------------------|
| * 9,067 | 98 | Driveway/Parking |
| 9,067 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 3S: Areas Routed to Retention


Summary for Subcatchment 4S: Areas Routed to Retention

Runoff = 1.29 cfs @ 12.11 hrs, Volume= 0.103 af, Depth> 3.30"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| | Area (sf) | CN | Description |
|---|-----------|----|-------------------------|
| * | 7,083 | 98 | Parking/Driveway |
| * | 5,245 | 98 | Building Units 2-4 |
| * | 4,017 | 98 | Building Units 8-10 |
| | 16,345 | 98 | Weighted Average |
| | 16,345 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 4S: Areas Routed to Retention


Summary for Subcatchment 5S: Areas not Routed to Retention

Runoff = 1.64 cfs @ 12.16 hrs, Volume= 0.132 af, Depth> 1.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 4,920 | 98 | Buildings |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 63,585 | 71 | Weighted Average |
| | 58,665 | | 92.26% Pervious Area |
| | 4,920 | | 7.74% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 5S: Areas not Routed to Retention

Summary for Pond 1P: 48" Concrete Galleries

Inflow Area = 0.583 ac, 100.00% Impervious, Inflow Depth > 1.18" for 2 Year event
 Inflow = 0.72 cfs @ 12.11 hrs, Volume= 0.057 af
 Outflow = 0.11 cfs @ 11.60 hrs, Volume= 0.057 af, Atten= 85%, Lag= 0.0 min
 Discarded = 0.11 cfs @ 11.60 hrs, Volume= 0.057 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 94.79' @ 12.62 hrs Surf.Area= 756 sf Storage= 612 cf

Plug-Flow detention time= 34.0 min calculated for 0.057 af (100% of inflow)
 Center-of-Mass det. time= 33.3 min (788.0 - 754.7)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 93.90' | 270 cf | 18.00'W x 42.00'L x 4.00'H Stone 3,024 cf Overall - 2,349 cf Embedded = 675 cf x 40.0% Voids |
| #2 | 93.90' | 2,349 cf | 16.00'W x 40.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 2,619 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Primary | 97.90' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 93.90' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.11 cfs @ 11.60 hrs HW=93.94' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=93.90' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 1P: 48" Concrete Galleries



Summary for Pond 2P: 48" Concrete Galleries

Inflow Area = 0.375 ac, 100.00% Impervious, Inflow Depth > 3.30" for 2 Year event
 Inflow = 1.29 cfs @ 12.11 hrs, Volume= 0.103 af
 Outflow = 0.13 cfs @ 11.24 hrs, Volume= 0.103 af, Atten= 90%, Lag= 0.0 min
 Discarded = 0.13 cfs @ 11.24 hrs, Volume= 0.103 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 100.32' @ 13.03 hrs Surf.Area= 900 sf Storage= 1,415 cf

Plug-Flow detention time= 74.5 min calculated for 0.103 af (100% of inflow)
 Center-of-Mass det. time= 73.8 min (828.5 - 754.7)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 98.60' | 313 cf | 18.00'W x 50.00'L x 4.00'H Stone 3,600 cf Overall - 2,819 cf Embedded = 781 cf x 40.0% Voids |
| #2 | 98.60' | 2,819 cf | 16.00'W x 48.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 3,131 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|---------|--|
| #1 | Primary | 102.60' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 98.60' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.13 cfs @ 11.24 hrs HW=98.64' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=98.60' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 2P: 48" Concrete Galleries




Summary for Link 1L: Combined Hydrograph

Inflow Area = 2.043 ac, 34.08% Impervious, Inflow Depth > 0.78" for 2 Year event
Inflow = 1.64 cfs @ 12.16 hrs, Volume= 0.132 af
Primary = 1.64 cfs @ 12.16 hrs, Volume= 0.132 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph




Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 0.93 cfs @ 12.11 hrs, Volume= 0.075 af, Depth> 4.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| Area (sf) | CN | Description |
|-----------|----|-------------------------|
| * 9,067 | 98 | Driveway/Parking |
| 9,067 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 3S: Areas Routed to Retention


Summary for Subcatchment 4S: Areas Routed to Retention

Runoff = 1.67 cfs @ 12.11 hrs, Volume= 0.135 af, Depth> 4.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| | Area (sf) | CN | Description |
|---|-----------|----|-------------------------|
| * | 7,083 | 98 | Parking/Driveway |
| * | 5,245 | 98 | Building Units 2-4 |
| * | 4,017 | 98 | Building Units 8-10 |
| | 16,345 | 98 | Weighted Average |
| | 16,345 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 4S: Areas Routed to Retention


Summary for Subcatchment 5S: Areas not Routed to Retention

Runoff = 2.76 cfs @ 12.16 hrs, Volume= 0.216 af, Depth> 1.78"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 4,920 | 98 | Buildings |
| 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| 63,585 | 71 | Weighted Average |
| 58,665 | | 92.26% Pervious Area |
| 4,920 | | 7.74% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 5S: Areas not Routed to Retention

Summary for Pond 1P: 48" Concrete Galleries

Inflow Area = 0.583 ac, 100.00% Impervious, Inflow Depth > 1.54" for 5 Year event
 Inflow = 0.93 cfs @ 12.11 hrs, Volume= 0.075 af
 Outflow = 0.11 cfs @ 11.40 hrs, Volume= 0.075 af, Atten= 89%, Lag= 0.0 min
 Discarded = 0.11 cfs @ 11.40 hrs, Volume= 0.075 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 95.24' @ 12.86 hrs Surf.Area= 756 sf Storage= 923 cf

Plug-Flow detention time= 54.4 min calculated for 0.075 af (100% of inflow)
 Center-of-Mass det. time= 53.8 min (803.5 - 749.6)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 93.90' | 270 cf | 18.00'W x 42.00'L x 4.00'H Stone 3,024 cf Overall - 2,349 cf Embedded = 675 cf x 40.0% Voids |
| #2 | 93.90' | 2,349 cf | 16.00'W x 40.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 2,619 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Primary | 97.90' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 93.90' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.11 cfs @ 11.40 hrs HW=93.94' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=93.90' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 1P: 48" Concrete Galleries



Summary for Pond 2P: 48" Concrete Galleries

Inflow Area = 0.375 ac, 100.00% Impervious, Inflow Depth > 4.31" for 5 Year event
 Inflow = 1.67 cfs @ 12.11 hrs, Volume= 0.135 af
 Outflow = 0.13 cfs @ 10.96 hrs, Volume= 0.135 af, Atten= 93%, Lag= 0.0 min
 Discarded = 0.13 cfs @ 10.96 hrs, Volume= 0.135 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 101.16' @ 13.31 hrs Surf.Area= 900 sf Storage= 2,097 cf

Plug-Flow detention time= 118.5 min calculated for 0.135 af (100% of inflow)
 Center-of-Mass det. time= 118.0 min (867.6 - 749.6)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 98.60' | 313 cf | 18.00'W x 50.00'L x 4.00'H Stone 3,600 cf Overall - 2,819 cf Embedded = 781 cf x 40.0% Voids |
| #2 | 98.60' | 2,819 cf | 16.00'W x 48.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 3,131 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|---------|--|
| #1 | Primary | 102.60' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 98.60' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.13 cfs @ 10.96 hrs HW=98.64' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=98.60' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 2P: 48" Concrete Galleries




Summary for Link 1L: Combined Hydrograph

Inflow Area = 2.043 ac, 34.08% Impervious, Inflow Depth > 1.27" for 5 Year event
Inflow = 2.76 cfs @ 12.16 hrs, Volume= 0.216 af
Primary = 2.76 cfs @ 12.16 hrs, Volume= 0.216 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph




Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 1.10 cfs @ 12.11 hrs, Volume= 0.089 af, Depth> 5.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| Area (sf) | CN | Description |
|-----------|----|-------------------------|
| * 9,067 | 98 | Driveway/Parking |
| 9,067 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 3S: Areas Routed to Retention


Summary for Subcatchment 4S: Areas Routed to Retention

Runoff = 1.98 cfs @ 12.11 hrs, Volume= 0.161 af, Depth> 5.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| | Area (sf) | CN | Description |
|---|-----------|----|-------------------------|
| * | 7,083 | 98 | Parking/Driveway |
| * | 5,245 | 98 | Building Units 2-4 |
| * | 4,017 | 98 | Building Units 8-10 |
| | 16,345 | 98 | Weighted Average |
| | 16,345 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 4S: Areas Routed to Retention


Summary for Subcatchment 5S: Areas not Routed to Retention

Runoff = 3.78 cfs @ 12.16 hrs, Volume= 0.293 af, Depth> 2.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 4,920 | 98 | Buildings |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 63,585 | 71 | Weighted Average |
| | 58,665 | | 92.26% Pervious Area |
| | 4,920 | | 7.74% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 5S: Areas not Routed to Retention

Summary for Pond 1P: 48" Concrete Galleries

Inflow Area = 0.583 ac, 100.00% Impervious, Inflow Depth > 1.84" for 10 Year event
 Inflow = 1.10 cfs @ 12.11 hrs, Volume= 0.089 af
 Outflow = 0.11 cfs @ 11.24 hrs, Volume= 0.089 af, Atten= 90%, Lag= 0.0 min
 Discarded = 0.11 cfs @ 11.24 hrs, Volume= 0.089 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 95.67' @ 13.04 hrs Surf.Area= 756 sf Storage= 1,213 cf

Plug-Flow detention time= 75.1 min calculated for 0.089 af (100% of inflow)
 Center-of-Mass det. time= 74.4 min (821.0 - 746.6)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 93.90' | 270 cf | 18.00'W x 42.00'L x 4.00'H Stone 3,024 cf Overall - 2,349 cf Embedded = 675 cf x 40.0% Voids |
| #2 | 93.90' | 2,349 cf | 16.00'W x 40.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 2,619 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Primary | 97.90' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 93.90' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.11 cfs @ 11.24 hrs HW=93.94' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=93.90' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 1P: 48" Concrete Galleries



Summary for Pond 2P: 48" Concrete Galleries

Inflow Area = 0.375 ac, 100.00% Impervious, Inflow Depth > 5.15" for 10 Year event
 Inflow = 1.98 cfs @ 12.11 hrs, Volume= 0.161 af
 Outflow = 0.13 cfs @ 10.76 hrs, Volume= 0.161 af, Atten= 94%, Lag= 0.0 min
 Discarded = 0.13 cfs @ 10.76 hrs, Volume= 0.161 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 101.90' @ 13.51 hrs Surf.Area= 900 sf Storage= 2,708 cf

Plug-Flow detention time= 161.5 min calculated for 0.161 af (100% of inflow)
 Center-of-Mass det. time= 160.6 min (907.2 - 746.6)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 98.60' | 313 cf | 18.00'W x 50.00'L x 4.00'H Stone 3,600 cf Overall - 2,819 cf Embedded = 781 cf x 40.0% Voids |
| #2 | 98.60' | 2,819 cf | 16.00'W x 48.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 3,131 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|---------|--|
| #1 | Primary | 102.60' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 98.60' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.13 cfs @ 10.76 hrs HW=98.64' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=98.60' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 2P: 48" Concrete Galleries




Summary for Link 1L: Combined Hydrograph

Inflow Area = 2.043 ac, 34.08% Impervious, Inflow Depth > 1.72" for 10 Year event
Inflow = 3.78 cfs @ 12.16 hrs, Volume= 0.293 af
Primary = 3.78 cfs @ 12.16 hrs, Volume= 0.293 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph




Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 1.34 cfs @ 12.11 hrs, Volume= 0.109 af, Depth> 6.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| Area (sf) | CN | Description |
|-----------|----|-------------------------|
| * 9,067 | 98 | Driveway/Parking |
| 9,067 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 3S: Areas Routed to Retention


Summary for Subcatchment 4S: Areas Routed to Retention

Runoff = 2.41 cfs @ 12.11 hrs, Volume= 0.197 af, Depth> 6.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| | Area (sf) | CN | Description |
|---|-----------|----|-------------------------|
| * | 7,083 | 98 | Parking/Driveway |
| * | 5,245 | 98 | Building Units 2-4 |
| * | 4,017 | 98 | Building Units 8-10 |
| | 16,345 | 98 | Weighted Average |
| | 16,345 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 4S: Areas Routed to Retention


Summary for Subcatchment 5S: Areas not Routed to Retention

Runoff = 5.24 cfs @ 12.16 hrs, Volume= 0.406 af, Depth> 3.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 4,920 | 98 | Buildings |
| 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| 63,585 | 71 | Weighted Average |
| 58,665 | | 92.26% Pervious Area |
| 4,920 | | 7.74% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 5S: Areas not Routed to Retention

Summary for Pond 1P: 48" Concrete Galleries

Inflow Area = 0.583 ac, 100.00% Impervious, Inflow Depth > 2.47" for 25 Year event
 Inflow = 1.34 cfs @ 12.11 hrs, Volume= 0.120 af
 Outflow = 0.11 cfs @ 11.00 hrs, Volume= 0.120 af, Atten= 92%, Lag= 0.0 min
 Discarded = 0.11 cfs @ 11.00 hrs, Volume= 0.120 af
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0.000 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 96.94' @ 13.55 hrs Surf.Area= 756 sf Storage= 2,085 cf

Plug-Flow detention time= 140.9 min calculated for 0.120 af (100% of inflow)
 Center-of-Mass det. time= 140.1 min (886.1 - 746.0)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 93.90' | 270 cf | 18.00'W x 42.00'L x 4.00'H Stone 3,024 cf Overall - 2,349 cf Embedded = 675 cf x 40.0% Voids |
| #2 | 93.90' | 2,349 cf | 16.00'W x 40.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 2,619 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Primary | 97.90' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 93.90' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.11 cfs @ 11.00 hrs HW=93.94' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.00 cfs @ 0.00 hrs HW=93.90' (Free Discharge)
 ↑1=Orifice/Grate (Controls 0.00 cfs)

Pond 1P: 48" Concrete Galleries



Summary for Pond 2P: 48" Concrete Galleries

Inflow Area = 0.375 ac, 100.00% Impervious, Inflow Depth > 6.31" for 25 Year event
 Inflow = 2.41 cfs @ 12.11 hrs, Volume= 0.197 af
 Outflow = 0.57 cfs @ 12.56 hrs, Volume= 0.188 af, Atten= 76%, Lag= 26.6 min
 Discarded = 0.13 cfs @ 10.40 hrs, Volume= 0.177 af
 Primary = 0.45 cfs @ 12.56 hrs, Volume= 0.011 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 102.83' @ 12.56 hrs Surf.Area= 900 sf Storage= 3,131 cf

Plug-Flow detention time= 187.5 min calculated for 0.187 af (95% of inflow)
 Center-of-Mass det. time= 157.9 min (901.3 - 743.5)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 98.60' | 313 cf | 18.00'W x 50.00'L x 4.00'H Stone 3,600 cf Overall - 2,819 cf Embedded = 781 cf x 40.0% Voids |
| #2 | 98.60' | 2,819 cf | 16.00'W x 48.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 3,131 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|---------|--|
| #1 | Primary | 102.60' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 98.60' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.13 cfs @ 10.40 hrs HW=98.64' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=0.44 cfs @ 12.56 hrs HW=102.82' (Free Discharge)
 ↑1=Orifice/Grate (Orifice Controls 0.44 cfs @ 2.24 fps)

Pond 2P: 48" Concrete Galleries




Summary for Link 1L: Combined Hydrograph

Inflow Area = 2.043 ac, 34.08% Impervious, Inflow Depth > 2.39" for 25 Year event
Inflow = 5.24 cfs @ 12.16 hrs, Volume= 0.406 af
Primary = 5.24 cfs @ 12.16 hrs, Volume= 0.406 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph




Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 1.52 cfs @ 12.11 hrs, Volume= 0.125 af, Depth> 7.20"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| Area (sf) | CN | Description |
|-----------|----|-------------------------|
| * 9,067 | 98 | Driveway/Parking |
| 9,067 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 3S: Areas Routed to Retention


Summary for Subcatchment 4S: Areas Routed to Retention

Runoff = 2.74 cfs @ 12.11 hrs, Volume= 0.225 af, Depth> 7.20"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| | Area (sf) | CN | Description |
|---|-----------|----|-------------------------|
| * | 7,083 | 98 | Parking/Driveway |
| * | 5,245 | 98 | Building Units 2-4 |
| * | 4,017 | 98 | Building Units 8-10 |
| | 16,345 | 98 | Weighted Average |
| | 16,345 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 4S: Areas Routed to Retention

Summary for Subcatchment 5S: Areas not Routed to Retention


Runoff = 6.41 cfs @ 12.16 hrs, Volume= 0.497 af, Depth> 4.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 4,920 | 98 | Buildings |
| | 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 63,585 | 71 | Weighted Average |
| | 58,665 | | 92.26% Pervious Area |
| | 4,920 | | 7.74% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 5S: Areas not Routed to Retention



Summary for Pond 1P: 48" Concrete Galleries

Inflow Area = 0.583 ac, 100.00% Impervious, Inflow Depth > 3.13" for 50 Year event
 Inflow = 1.94 cfs @ 12.28 hrs, Volume= 0.152 af
 Outflow = 0.47 cfs @ 12.72 hrs, Volume= 0.152 af, Atten= 76%, Lag= 26.4 min
 Discarded = 0.11 cfs @ 10.84 hrs, Volume= 0.140 af
 Primary = 0.36 cfs @ 12.72 hrs, Volume= 0.012 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 98.07' @ 12.72 hrs Surf.Area= 756 sf Storage= 2,619 cf

Plug-Flow detention time= 173.8 min calculated for 0.152 af (100% of inflow)
 Center-of-Mass det. time= 173.2 min (918.0 - 744.8)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 93.90' | 270 cf | 18.00'W x 42.00'L x 4.00'H Stone 3,024 cf Overall - 2,349 cf Embedded = 675 cf x 40.0% Voids |
| #2 | 93.90' | 2,349 cf | 16.00'W x 40.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 2,619 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Primary | 97.90' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 93.90' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.11 cfs @ 10.84 hrs HW=93.94' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=0.36 cfs @ 12.72 hrs HW=98.07' (Free Discharge)
 ↑1=Orifice/Grate (Weir Controls 0.36 cfs @ 1.35 fps)

Pond 1P: 48" Concrete Galleries



Summary for Pond 2P: 48" Concrete Galleries

Inflow Area = 0.375 ac, 100.00% Impervious, Inflow Depth > 7.20" for 50 Year event
 Inflow = 2.74 cfs @ 12.11 hrs, Volume= 0.225 af
 Outflow = 1.57 cfs @ 12.28 hrs, Volume= 0.210 af, Atten= 43%, Lag= 9.8 min
 Discarded = 0.13 cfs @ 10.04 hrs, Volume= 0.183 af
 Primary = 1.44 cfs @ 12.28 hrs, Volume= 0.027 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 104.92' @ 12.28 hrs Surf.Area= 900 sf Storage= 3,131 cf

Plug-Flow detention time= 173.5 min calculated for 0.210 af (93% of inflow)
 Center-of-Mass det. time= 134.4 min (876.0 - 741.6)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 98.60' | 313 cf | 18.00'W x 50.00'L x 4.00'H Stone 3,600 cf Overall - 2,819 cf Embedded = 781 cf x 40.0% Voids |
| #2 | 98.60' | 2,819 cf | 16.00'W x 48.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 3,131 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|---------|--|
| #1 | Primary | 102.60' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 98.60' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.13 cfs @ 10.04 hrs HW=98.64' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=1.40 cfs @ 12.28 hrs HW=104.79' (Free Discharge)
 ↑1=Orifice/Grate (Orifice Controls 1.40 cfs @ 7.12 fps)

Pond 2P: 48" Concrete Galleries




Summary for Link 1L: Combined Hydrograph

Inflow Area = 2.043 ac, 34.08% Impervious, Inflow Depth > 2.99" for 50 Year event
Inflow = 6.41 cfs @ 12.16 hrs, Volume= 0.510 af
Primary = 6.41 cfs @ 12.16 hrs, Volume= 0.510 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph




Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 1.71 cfs @ 12.11 hrs, Volume= 0.140 af, Depth> 8.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"

| Area (sf) | CN | Description |
|-----------|----|-------------------------|
| * 9,067 | 98 | Driveway/Parking |
| 9,067 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 3S: Areas Routed to Retention


Summary for Subcatchment 4S: Areas Routed to Retention

Runoff = 3.07 cfs @ 12.11 hrs, Volume= 0.253 af, Depth> 8.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"

| | Area (sf) | CN | Description |
|---|-----------|----|-------------------------|
| * | 7,083 | 98 | Parking/Driveway |
| * | 5,245 | 98 | Building Units 2-4 |
| * | 4,017 | 98 | Building Units 8-10 |
| | 16,345 | 98 | Weighted Average |
| | 16,345 | | 100.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|-------------|------------------|------------------|----------------------|-------------------|----------------------|
| 5.0 | | | | | Direct Entry, Direct |

Subcatchment 4S: Areas Routed to Retention


Summary for Subcatchment 5S: Areas not Routed to Retention

Runoff = 7.60 cfs @ 12.15 hrs, Volume= 0.592 af, Depth> 4.87"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 4,920 | 98 | Buildings |
| 58,665 | 69 | 50-75% Grass cover, Fair, HSG B |
| 63,585 | 71 | Weighted Average |
| 58,665 | | 92.26% Pervious Area |
| 4,920 | | 7.74% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 6.3 | 111 | 0.0650 | 0.29 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 1.9 | 250 | 0.1020 | 2.24 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 8.2 | 361 | Total | | | |

Subcatchment 5S: Areas not Routed to Retention

Summary for Pond 1P: 48" Concrete Galleries

Inflow Area = 0.583 ac, 100.00% Impervious, Inflow Depth > 3.84" for 100 Year event
 Inflow = 3.39 cfs @ 12.19 hrs, Volume= 0.186 af
 Outflow = 1.99 cfs @ 12.32 hrs, Volume= 0.184 af, Atten= 41%, Lag= 8.1 min
 Discarded = 0.11 cfs @ 10.72 hrs, Volume= 0.145 af
 Primary = 1.89 cfs @ 12.32 hrs, Volume= 0.039 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 101.89' @ 12.32 hrs Surf.Area= 756 sf Storage= 2,619 cf

Plug-Flow detention time= 154.1 min calculated for 0.184 af (98% of inflow)
 Center-of-Mass det. time= 143.9 min (887.4 - 743.5)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 93.90' | 270 cf | 18.00'W x 42.00'L x 4.00'H Stone 3,024 cf Overall - 2,349 cf Embedded = 675 cf x 40.0% Voids |
| #2 | 93.90' | 2,349 cf | 16.00'W x 40.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 2,619 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|--------|--|
| #1 | Primary | 97.90' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 93.90' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.11 cfs @ 10.72 hrs HW=93.94' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.11 cfs)

Primary OutFlow Max=1.88 cfs @ 12.32 hrs HW=101.84' (Free Discharge)
 ↑1=Orifice/Grate (Orifice Controls 1.88 cfs @ 9.56 fps)

Pond 1P: 48" Concrete Galleries



Summary for Pond 2P: 48" Concrete Galleries

Inflow Area = 0.375 ac, 100.00% Impervious, Inflow Depth > 8.09" for 100 Year event
 Inflow = 3.07 cfs @ 12.11 hrs, Volume= 0.253 af
 Outflow = 2.51 cfs @ 12.19 hrs, Volume= 0.233 af, Atten= 18%, Lag= 4.7 min
 Discarded = 0.13 cfs @ 9.80 hrs, Volume= 0.187 af
 Primary = 2.39 cfs @ 12.19 hrs, Volume= 0.046 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
 Peak Elev= 108.70' @ 12.19 hrs Surf.Area= 900 sf Storage= 3,131 cf

Plug-Flow detention time= 161.2 min calculated for 0.233 af (92% of inflow)
 Center-of-Mass det. time= 116.2 min (856.3 - 740.1)


| Volume | Invert | Avail.Storage | Storage Description |
|--------|--------|---------------|--|
| #1 | 98.60' | 313 cf | 18.00'W x 50.00'L x 4.00'H Stone 3,600 cf Overall - 2,819 cf Embedded = 781 cf x 40.0% Voids |
| #2 | 98.60' | 2,819 cf | 16.00'W x 48.00'L x 3.67'H 48" Concrete Galleries Inside #1 |
| | | 3,131 cf | Total Available Storage |

| Device | Routing | Invert | Outlet Devices |
|--------|-----------|---------|--|
| #1 | Primary | 102.60' | 6.0" Horiz. Orifice/Grate C= 0.600 Limited to weir flow at low heads |
| #2 | Discarded | 98.60' | 6.000 in/hr Exfiltration over Horizontal area |

Discarded OutFlow Max=0.13 cfs @ 9.80 hrs HW=98.68' (Free Discharge)
 ↑2=Exfiltration (Exfiltration Controls 0.13 cfs)

Primary OutFlow Max=2.17 cfs @ 12.19 hrs HW=107.88' (Free Discharge)
 ↑1=Orifice/Grate (Orifice Controls 2.17 cfs @ 11.06 hrs)

Pond 2P: 48" Concrete Galleries




Summary for Link 1L: Combined Hydrograph

Inflow Area = 2.043 ac, 34.08% Impervious, Inflow Depth > 3.71" for 100 Year event
Inflow = 7.60 cfs @ 12.15 hrs, Volume= 0.631 af
Primary = 7.60 cfs @ 12.15 hrs, Volume= 0.631 af, Atten= 0%, Lag= 0.0 min


Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph





APPENDIX “D”

HYDROCAD ANALYSIS BASIN B CT ROUTE 32



Existing Conditions

Basin B Route 32



Routing Diagram for 2578Existing

Prepared by Fairfield County Engineering LLC, Printed 4/17/2025
HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC


Summary for Subcatchment 1S: Existing Conditions Basin B Route 32

Runoff = 0.76 cfs @ 12.13 hrs, Volume= 0.054 af, Depth> 1.33"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,659 | 98 | House |
| * 1,934 | 98 | Driveway |
| * 836 | 85 | Gravel |
| * 196 | 98 | Walks |
| 16,768 | 69 | 50-75% Grass cover, Fair, HSG B |
| 21,393 | 75 | Weighted Average |
| 17,604 | | 82.29% Pervious Area |
| 3,789 | | 17.71% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 1S: Existing Conditions Basin B Route 32


Summary for Subcatchment 1S: Existing Conditions Basin B Route 32

Runoff = 1.21 cfs @ 12.12 hrs, Volume= 0.085 af, Depth> 2.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,659 | 98 | House |
| * | 1,934 | 98 | Driveway |
| * | 836 | 85 | Gravel |
| * | 196 | 98 | Walks |
| | 16,768 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 21,393 | 75 | Weighted Average |
| | 17,604 | | 82.29% Pervious Area |
| | 3,789 | | 17.71% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 1S: Existing Conditions Basin B Route 32


Summary for Subcatchment 1S: Existing Conditions Basin B Route 32

Runoff = 1.61 cfs @ 12.12 hrs, Volume= 0.113 af, Depth> 2.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,659 | 98 | House |
| * | 1,934 | 98 | Driveway |
| * | 836 | 85 | Gravel |
| * | 196 | 98 | Walks |
| | 16,768 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 21,393 | 75 | Weighted Average |
| | 17,604 | | 82.29% Pervious Area |
| | 3,789 | | 17.71% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 1S: Existing Conditions Basin B Route 32


Summary for Subcatchment 1S: Existing Conditions Basin B Route 32

Runoff = 2.17 cfs @ 12.12 hrs, Volume= 0.154 af, Depth> 3.75"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,659 | 98 | House |
| * | 1,934 | 98 | Driveway |
| * | 836 | 85 | Gravel |
| * | 196 | 98 | Walks |
| | 16,768 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 21,393 | 75 | Weighted Average |
| | 17,604 | | 82.29% Pervious Area |
| | 3,789 | | 17.71% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 1S: Existing Conditions Basin B Route 32


Summary for Subcatchment 1S: Existing Conditions Basin B Route 32

Runoff = 2.61 cfs @ 12.12 hrs, Volume= 0.186 af, Depth> 4.53"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,659 | 98 | House |
| * | 1,934 | 98 | Driveway |
| * | 836 | 85 | Gravel |
| * | 196 | 98 | Walks |
| | 16,768 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 21,393 | 75 | Weighted Average |
| | 17,604 | | 82.29% Pervious Area |
| | 3,789 | | 17.71% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 1S: Existing Conditions Basin B Route 32


Summary for Subcatchment 1S: Existing Conditions Basin B Route 32


Runoff = 3.06 cfs @ 12.12 hrs, Volume= 0.219 af, Depth> 5.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"



| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,659 | 98 | House |
| * | 1,934 | 98 | Driveway |
| * | 836 | 85 | Gravel |
| * | 196 | 98 | Walks |
| | 16,768 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 21,393 | 75 | Weighted Average |
| | 17,604 | | 82.29% Pervious Area |
| | 3,789 | | 17.71% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 1S: Existing Conditions Basin B Route 32



Proposed Conditions Basin B Route 32



Routing Diagram for 2578Proposed
Prepared by Fairfield County Engineering LLC, Printed 4/17/2025
HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC

2578Proposed

Prepared by Fairfield County Engineering LLC

HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC

NOAA 24-hr D 2 Year Rainfall=3.54"

Printed 4/17/2025

Page 66


Summary for Subcatchment 2S: Proposed Conditions Basin B Route 32

Runoff = 0.74 cfs @ 12.13 hrs, Volume= 0.053 af, Depth> 1.33"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 2 Year Rainfall=3.54"

| | Area (sf) | CN | Description |
|---|-----------|----|---------------------------------|
| * | 1,659 | 98 | House |
| * | 1,046 | 98 | Building |
| * | 1,271 | 98 | Driveway |
| | 16,694 | 69 | 50-75% Grass cover, Fair, HSG B |
| | 20,670 | 75 | Weighted Average |
| | 16,694 | | 80.76% Pervious Area |
| | 3,976 | | 19.24% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin B Route 32


Summary for Subcatchment 2S: Proposed Conditions Basin B Route 32

Runoff = 1.17 cfs @ 12.12 hrs, Volume= 0.083 af, Depth> 2.09"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 5 Year Rainfall=4.55"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,659 | 98 | House |
| * 1,046 | 98 | Building |
| * 1,271 | 98 | Driveway |
| 16,694 | 69 | 50-75% Grass cover, Fair, HSG B |
| 20,670 | 75 | Weighted Average |
| 16,694 | | 80.76% Pervious Area |
| 3,976 | | 19.24% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin B Route 32


Summary for Subcatchment 2S: Proposed Conditions Basin B Route 32

Runoff = 1.55 cfs @ 12.12 hrs, Volume= 0.109 af, Depth> 2.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 10 Year Rainfall=5.39"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,659 | 98 | House |
| * 1,046 | 98 | Building |
| * 1,271 | 98 | Driveway |
| 16,694 | 69 | 50-75% Grass cover, Fair, HSG B |
| 20,670 | 75 | Weighted Average |
| 16,694 | | 80.76% Pervious Area |
| 3,976 | | 19.24% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin B Route 32


Summary for Subcatchment 2S: Proposed Conditions Basin B Route 32

Runoff = 2.10 cfs @ 12.12 hrs, Volume= 0.148 af, Depth> 3.75"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 25 Year Rainfall=6.55"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,659 | 98 | House |
| * 1,046 | 98 | Building |
| * 1,271 | 98 | Driveway |
| 16,694 | 69 | 50-75% Grass cover, Fair, HSG B |
| 20,670 | 75 | Weighted Average |
| 16,694 | | 80.76% Pervious Area |
| 3,976 | | 19.24% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin B Route 32


Summary for Subcatchment 2S: Proposed Conditions Basin B Route 32

Runoff = 2.52 cfs @ 12.12 hrs, Volume= 0.179 af, Depth> 4.53"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 50 Year Rainfall=7.44"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,659 | 98 | House |
| * 1,046 | 98 | Building |
| * 1,271 | 98 | Driveway |
| 16,694 | 69 | 50-75% Grass cover, Fair, HSG B |
| 20,670 | 75 | Weighted Average |
| 16,694 | | 80.76% Pervious Area |
| 3,976 | | 19.24% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |

Subcatchment 2S: Proposed Conditions Basin B Route 32


Summary for Subcatchment 2S: Proposed Conditions Basin B Route 32

Runoff = 2.95 cfs @ 12.12 hrs, Volume= 0.211 af, Depth> 5.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs
NOAA 24-hr D 100 Year Rainfall=8.34"

| Area (sf) | CN | Description |
|-----------|----|---------------------------------|
| * 1,659 | 98 | House |
| * 1,046 | 98 | Building |
| * 1,271 | 98 | Driveway |
| 16,694 | 69 | 50-75% Grass cover, Fair, HSG B |
| 20,670 | 75 | Weighted Average |
| 16,694 | | 80.76% Pervious Area |
| 3,976 | | 19.24% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description |
|----------|---------------|---------------|-------------------|----------------|---|
| 5.2 | 100 | 0.0850 | 0.32 | | Sheet Flow, Sheet Flow |
| | | | | | Grass: Short n= 0.150 P2= 3.54" |
| 0.3 | 31 | 0.0850 | 2.04 | | Shallow Concentrated Flow, Shallow Concentrated Flow |
| | | | | | Short Grass Pasture Kv= 7.0 fps |
| 5.5 | 131 | Total | | | |


Subcatchment 2S: Proposed Conditions Basin B Route 32

APPENDIX E

WATERSHED MAPS
FOR
EXISTING & PROPOSED CONDITIONS

GENERAL NOTES

1. STORMWATER RUNOFF ANALYSIS WAS CALCULATED USING THE NRCS TR-20 METHODOLOGY.



THIS DRAWING IS THE PROPERTY OF THE ENGINEER. IT HAS BEEN SPECIFICALLY PREPARED FOR THE OWNER FOR THIS PROJECT AT THIS SITE AND IS NOT TO BE USED FOR ANY OTHER PURPOSE, LOCATION OR OWNER WITHOUT WRITTEN CONSENT OF THE ENGINEER.



525 JOHN STREET BRIDGEPORT, CT. 06604
Office (203) 333-9485
fax (203) 336-1769
e-mail info@FullerSurveyors

MADISON PLACE
LUXURY TOWNHOUSE DEVELOPMENT
18 POWERHOUSE ROAD
MONTVILLE, CONNECTICUT
PREPARED FOR
JNE HOLDINGS, LLC

Job Number:
FE24-1889

Job Start Date:
3/20/24

| | |
|----------------|----------|
| Staff Comments | 04/18/25 |
| Staff Comments | 04/16/25 |
| Staff Comments | 03/31/25 |
| Staff Comments | 03/18/25 |
| Staff Comments | 03/07/25 |
| Staff Comments | 02/21/25 |
| Submission | 02/11/25 |

Drawn By: Checked By:
D.R.R. J.E.Q.

Sheet Title:
EXISTING
DRAINAGE AREA

Scale:
1" = 20'

Sheet Number:
DA-EX

LEGEND

PROPERTY LINE
LIMITS OF EXISTING DRAINAGE AREA
FLOW PATH

EXISTING DRAINAGE AREA 'A'
HYDROLOGIC SOIL GROUP B
TOTAL DRAINAGE AREA = 2.0 AC
TOTAL IMPERVIOUS AREA = 0.1 AC
TOTAL PERVIOUS AREA = 1.9 AC
CURVE NUMBER = 70
TIME OF CONCENTRATION = 17.1 MIN.

EXISTING DRAINAGE AREA 'B'
TOTAL DRAINAGE AREA = 21.393
TOTAL IMPERVIOUS AREA = 3,789 S.F.
TOTAL PERVIOUS AREA = 17,604 S.F.
CURVE NUMBER = 75
TIME OF CONCENTRATION = 5.5 MIN.


SHALLOW
CONCENTRATED
FLOW PATH = 199'

SHEET FLOW
PATH = 162'

FLOW PATH
122'



APPROVED BY THE MONTVILLE INLAND WETLAND COMMISSION
CHAIRMAN _____ DATE _____
APPROVED BY THE MONTVILLE PLANNING AND ZONING COMMISSION
CHAIRMAN _____ DATE _____
EXPIRATION DATE _____
SEC PLAN APPROVAL DATE _____



GENERAL NOTES

1. THE STORMWATER MANAGEMENT PLAN AND DESIGN IS INTENDED TO BE IN COMPLIANCE WITH THE 2000 CONNECTICUT DEPARTMENT OF TRANSPORTATION (CTDOT) DRAINAGE MANUAL AND THE 2004 CONNECTICUT STORMWATER QUALITY MANUAL.
2. STORMWATER RUNOFF ANALYSIS WAS CALCULATED USING THE SCS TR-55 METHODOLOGY.

LEGEND

- PROPERTY LINE
LIMITS OF EXISTING DRAINAGE AREA
FLOW PATH
AREA NOT ROUTED TO DETENTION

THIS DRAWING IS THE PROPERTY OF THE ENGINEER. IT HAS BEEN SPECIFICALLY PREPARED FOR THE OWNER FOR THIS PROJECT AT THIS SITE AND IS NOT TO BE USED FOR ANY OTHER PURPOSE, LOCATION OR OWNER WITHOUT WRITTEN CONSENT OF THE ENGINEER.



525 JOHN STREET BRIDGEPORT, CT 06604
Office (203) 333-9485
fax (203) 336-1769
e-mail info@FullerSurveyors

MADISON PLACE
LUXURY TOWNHOUSE DEVELOPMENT
18 POWERHOUSE ROAD
MONTVILLE, CONNECTICUT
PREPARED FOR
JNE HOLDINGS, LLC

Job Number:
FE24-1889

Job Start Date:
3/20/24


| | |
|----------------|----------|
| Staff Comments | 04/18/25 |
| Staff Comments | 04/16/25 |
| Staff Comments | 03/31/25 |
| Staff Comments | 03/18/25 |
| Staff Comments | 03/07/25 |
| Staff Comments | 02/21/25 |
| Submission | 02/11/25 |

Drawn By: Checked By:
D.R.R. J.E.Q.

Sheet Title:
PROPOSED DRAINAGE AREA

Scale:
1" = 20'

Sheet Number:
DA-PR



APPENDIX F
PIPE FLOW CALCULATIONS

FULLER ENGINEERING & LAND SURVEYING, LLC

525 John Street – Second Floor – Bridgeport, CT 06604

Phone: (203) 333-9465

Fax: (203) 336-1769

PIPE FLOW CALCULATIONS

Phase 1

8" pipe @ 1% = **1.43 cfs**

10" pipe @ 0.5 % = **1.83 cfs**

Therefore, good for Phase 1; max flow 0.85 cfs

Phase 2

8" pipe @ 3 % = **2.47 cfs**

8" pipe @ 1.5 % = **1.74 cfs**

Therefore, good for Phase 2 and 3 ; max flow 1.63 cfs

APPENDIX “G”

OPERATIONS AND MAINTENANCE PLAN

Appendix O

Operations and Maintenance Plan

*145 Norwich New London Tpke. Route 32 &
18 Powerhouse Road
Montville, CT*

February 11, 2025

Scope:

The purpose of the Operations and Maintenance Plan is to ensure that the existing and proposed stormwater components installed at *145 Route 32, Norwich New London Turnpike and 18 Powerhouse Road, Montville, CT* are maintained in operational condition throughout the life of the project. The service procedures associated with this plan shall be performed as required by the parties legally responsible for their maintenance.

Recommended Frequency of Service:

As further defined below, all stormwater components should be checked on a periodic basis and kept in full working order. Ultimately, the required frequency of inspection and service will depend on runoff quantities, pollutant loading, and clogging due to debris. At a minimum, we recommend that all stormwater components be inspected and serviced twice per year, once before winter begins and once during spring cleanup.

Qualified Inspector:

The inspections must be completed by an individual experienced in the construction and maintenance of stormwater drainage systems. Once every five years the inspections must be completed by a professional engineer.

Service Procedures:

1. **Catch Basins & Drainage Inlets:**
 - a. Catch basins and drainage inlets shall be completely cleaned of accumulated debris and sediments at the completion of construction.
 - b. For the first year, catch basins and drainage inlets shall be inspected on a quarterly basis.
 - c. Any accumulated debris within the catch basins/inlets shall be removed and any repairs as required.
 - d. From the second year onward, visual inspections shall occur twice per year, once in the spring and once in the fall, after fall cleanup of leaves has occurred.
 - e. Accumulated debris within the catch basins/inlets shall be removed and repairs made as required.
 - f. Accumulated sediments shall be removed at which time they are within 12 inches of the invert of the outlet pipe.
 - g. Any additional maintenance required per the manufacturer's specifications shall also be completed.
2. **Storm Drainage Piping and Manholes/Junction Boxes:**
 - a. All storm drainage piping shall be completely flushed of debris and accumulated sediment at the completion of construction.
 - b. Manholes/Junction Boxes shall be inspected and repaired on an annual basis.

- c. Unless system performance indicates degradation of piping, comprehensive video inspection of storm drainage piping shall occur once every ten years.
 - d. Any additional maintenance required per the manufacturer's specifications shall also be completed.
3. Stormwater Inlet/Control Structures:
- a. All control structures (orifice, weir, etc.) shall be completely cleaned of accumulated debris and sediments at the completion of construction. Any repairs shall be performed.
 - b. For the first year, control structures (orifice, weir, etc.) shall be inspected on a quarterly basis.
 - c. Any accumulated debris shall be removed and any repairs made to the control structures (orifice, weir, etc.) as required.
 - d. From the second year onward, visual inspections shall occur twice per year, once in the spring and once in the fall, after fall cleanup of leaves has occurred.
 - e. Accumulated debris shall be removed and repairs made as required.
 - f. Any additional maintenance required per the manufacturer's specifications shall also be completed.
4. Drywells and Infiltration Systems:
- a. All drywells/infiltrators shall be completely cleaned of accumulated debris and sediments upon the completion of construction.
 - b. For the first year, the drywells/infiltrators shall be inspected on a quarterly basis.
 - c. Any accumulated debris within the drywells/infiltrators shall be removed and any repairs made to the units as required.
 - d. From the second year onward, visual inspection shall occur twice per year, once in the spring and once in the fall, after fall cleanup of leaves has occurred.
 - e. Accumulated debris within the units shall be removed and repairs made as required.
 - f. Any additional maintenance required per the manufacturer's specifications shall also be completed.
5. Roof Gutters:
- a. Remove accumulated debris and inspect for damage. Any damage should be repaired as required.

Disposal of Debris and Sediment:

All debris and sediment removed from the stormwater structures and bioretention/biofiltration basins shall be disposed of legally. There shall be no dumping of silt or debris into or in proximity to any inland or tidal wetlands.

Maintenance Records:

The Owners(s) must maintain all records (logs, invoices, reports, data, etc.) and have them readily available for inspection at all times.

Operations and Maintenance Log (Page 1 of 3)

#245 Route 32 Norwich New London Tpke. Montville, CT

March 8, 2022 30,

Type of Inspection: ☐ Spring ☐ Fall ☐ Other

Inspector's Name: _____ Date of Inspection: _____

Affiliation: _____ Phone #: _____

Catch Basins & Drainage Inlets:

- Has accumulated debris been removed from grates? ☐ Yes ☐ No ☐ N/A
- Do any basins require additional repair? (identify below): ☐ Yes ☐ No ☐ N/A
- Have sumps been cleaned of sediment? ☐ Yes ☐ No ☐ N/A

Notes:

Storm Drainage Piping and Manholes/Junction Boxes:

- Has accumulated debris been removed? ☐ Yes ☐ No ☐ N/A
- Do any manholes require additional repair? (identify below): ☐ Yes ☐ No ☐ N/A
- Is there any evidence of stormwater piping failure? ☐ Yes ☐ No ☐ N/A
- Has a comprehensive video inspection been completed? ☐ Yes ☐ No ☐ N/A

Notes:

Stormwater Control Structures:

- Has accumulated debris been removed? ☐ Yes ☐ No ☐ N/A
- Are any repairs required? (identify below): ☐ Yes ☐ No ☐ N/A
- Have orifices and weirs been cleaned of debris? ☐ Yes ☐ No ☐ N/A

Notes:

Operations and Maintenance Log (Page 2 of 3)

#245 Route 32 Norwich New London Tpke., Montville, CT

March 8, 2022

Drainage Outfalls/Splash Pads/Scour Holes/Level Spreaders:

- Have all drainage outlets been cleared of debris? ☐ Yes ☐ No ☐ N/A
- Have all outlet protections been inspected/repared? ☐ Yes ☐ No ☐ N/A
- Have all erosion issues been repaired? ☐ Yes ☐ No ☐ N/A

Notes:

Drywells and Infiltration Systems:

- Have units been cleared of debris/sediments? ☐ Yes ☐ No ☐ N/A
- Do units require additional repair? (identify below): ☐ Yes ☐ No ☐ N/A
- Has draining times of system been verified? ☐ Yes ☐ No ☐ N/A

Notes:

Roof Gutters:

- Has accumulated debris been removed from gutters? ☐ Yes ☐ No ☐ N/A
- Do any gutters require additional repair? (identify below): ☐ Yes ☐ No ☐ N/A

Notes:

Operations and Maintenance Log (Page 3 of 3)

#245 Route 32 Norwich New London Tpke. Montville CT

March 8, 2022

Please make additional notes/observations and particular concerns below. Also record any additional maintenance that has been performed:

Signature of Inspector:

Date: